

# 52"/60"



Commercial performance is just the beginning.

## FEATURES

- 52" and 60" Commercial Side-Discharge deep decks
- Parker HTE Commercial Transmissions
- Premium Adjustable Seat
- Easy foot operated deck lift in 1/4in increments
- 7 & 11 gauge double plated commercial decks
- 9 mph
- 6.8 gallon fuel capacity
- 24" full size drive tires
- 13 x 6.5 front caster tires

**2** YEAR | **1200** HOUR  
LIMITED WARRANTY

OR

**5** YEAR | **500** HOUR  
LIMITED WARRANTY

\* See your local Hustler dealer for complete warranty details



\* Original Purchaser Only

[www.hustlerturf.com](http://www.hustlerturf.com)



**HUSTLER**   
Cutting Grass Not Corners



## Engines

<b>Kawasaki</b>	<b>Kawasaki</b>
FX691	FX730
22 hp	23.5 hp

# 52"/60"

### More Engine Information:

• [www.kawpower.com](http://www.kawpower.com)

#### ENGINE

**Starter:** 12-volt

**Ignition:** Electronic

**Charging System:** 12-volt (see engine manufacturer specs)

**Fuel:** Unleaded gasoline (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Air Cleaner:** Heavy-duty air cleaner to extend the service interval for excessive, dirty applications and improved performance

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

#### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic integrated transmissions.

**Drive Train:** Each Parker HTE10 transmission consists of a variable displacement piston pump driving a geroller (roller vane) style wheel motor.

**Pump Drive:** V-belt drive from engine crankshaft

**Hydraulic Lines:** No external hydraulic plumbing.

**Filter:** Internal for each transmission

**Ground Speed** (Infinitely variable)

**Forward:** 0-9 mph (0-14.5 kph)

**Reverse:** 0-5 mph (0-8 kph)

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning:** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

#### Brakes

**Service:** Hydrostatic dynamic braking

**Parking:** Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged.

#### Tires

**Front:** 13 x 6.5 – 6, rib tread, pneumatic

**Drive:** 52: 24 x 9.5 – 12, 60: 24 x 12.0 – 12

**Capacities Fuel System:** 6.8 US gal (25.74l)

#### GENERAL INFORMATION

**Safety Features:** Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck clutch and park brake switches. Stabilizer wheels at rear of lawn mower. Side discharge deck with discharge chute.

**Seat:** Deluxe vinyl seat with armrests. Fore and aft sliding adjustment.

**Construction:** Main frame is 1.5 in x 2.0 in x .188 in square steel tubing. Front caster wheels mounted with sealed ball bearings on each wheel. Front caster forks are .50 in (12.7 cm) steel

**PTO Clutch:** 200 ft. lbs.

**Controls:** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators:** Engine warning light (low oil pressure)

**Cup Holder:** Cup holder molded into the left side fuel tank.

**ROPS:** Certified, 2-post, foldable ROPS with seatbelt.

#### DIMENSIONS

**Height:** 52.8 in (134.11 cm) With ROPS folded

71.5 in (181.61 cm) With ROPS up

**W/52" Side-Discharge Deck**

**Length:** 81.75 in (207.65 cm)

**Overall width:** 57 in (144.78 cm) w/discharge chute up

**Tire-to-tire width:** 45.2 in (114.81 cm)

**Weight:** 1025 lbs (465 kg)

**W/60" Side-Discharge Deck**

**Length:** 81.75 in (207.65 cm)

**Overall width:** 66 in (168 cm) w/discharge chute up

**Tire-to-tire width:** 49.3 in (125.22 cm)

**Weight:** 1075 lbs (488 kg)

#### DECKS

**Side-Discharge:** 52" or 60"

**Type:** Free-floating mower deck using three blades with center blade to the front. Includes 3 deck-mounted rollers to improve flotation in rolling and uneven terrain

**Deck Lift:** Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climbing curbs and trailer more easily.

**Construction:** Welded steel. Solid 1.5 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge. Reinforcements welded onto spindle mount areas. High density, rubberized discharge chute.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.0 in to 5.5 in (3.81 cm to 13.97 cm)

**Mowing Blades:** Heavy-duty, heat-treated, high-lift steel blades.  
52 in: 17.9 in x 2.5 in x .20 in  
60 in: 20.9 in x 2.5 in x .20 in

**Blade Tip Speed** (at 3600 RPM engine speed)

Side-Discharge

52 in: 17,710 fpm

60 in: 18,410 fpm

**Deck Drive:** Single V-belt drive from engine with electric clutch to all three spindles. Spring tension idler and large pulleys to extend belt life.

**Spindles:** Ductile iron casting with steel shafts and sealed ball bearings

#### Width of Cut

Side-Discharge

52 in: 51.25 in

60 in: 59.25 in

**Trim Capacity** (left side)

52 in: 2.5 in (6.5 cm) w/9.5 in tire

60 in: 6.2 in (15.7 cm) w/12 in tire

#### ACCESSORIES

**Flex Forks™:** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Semi-Pneumatic tires**

**Gator™ Blades:** Patented mulching blade design

**Wavy Blades:** Improved performance for mulching

**Other Accessories:** Light Kit, Steering Lever Extension Kit, Suspension Kit for seat.

*Specifications subject to change without notice.*

