

# 42"

## **ZEON**

Just unplug and mow!

### FEATURES

- World's first electric zero-turning radius riding mower!
- Able to mow over 1 acre on a single charge!
- Green friendly - zero emissions
- Nearly zero maintenance
- Clean and neat - no belts, filters, fluids, etc.
- No engine noise - much quieter than gasoline-powered equipment!
- SmoothTrak™ Steering w/ patented automatic park brake system
- Heavy Duty welded steel deck and tubular frame.
- 42" side-discharge/mulching deck
- 18" drive tires, 11" caster tires
- Standard, Certified ROPS and seat belt

### WARRANTY

**3** YEAR | **LIMITED**  
RESIDENTIAL

OR

### WARRANTY

**1** YEAR | **LIMITED**  
COMMERCIAL

\* See your local Hustler dealer for complete warranty details

[www.hustlerturf.com](http://www.hustlerturf.com)



**HUSTLER®**  
Cutting Grass Not Corners





## 48-volt/42-inch side-discharge deck

# 42"

**Charge Time** 16 hours (standard charger)

### TRACTION DRIVE SYSTEM

#### Ground Speed

Forward: 0-6 mph (0-9.65 kph) infinitely variable  
Reverse: 0-3 mph (0-4.8 kph) infinitely variable

**Steering** Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-radius turns are all controlled with hand-operated controls

**Turning Radius** True zero radius. Turns within its own length. Counter-rotating, independent drive wheels

#### Brakes

Service: Dynamic braking  
Parking: Internal Cog

**Tires** Front: Two – 11 x 4 – 5, smooth, pneumatic  
Drive: 18 x 8.50 – 8, turf tread

### GENERAL INFORMATION

**Safety Features** Operator presence safety-interlock system. Side discharge deck with discharge chute

**Seat** Molded-vinyl seat. Fore and aft adjustment. Seat-pan suspension springs standard.

**Construction** Mainframe is 1.50 x 2.00 x .120 wall steel tubing.

**Controls** Hand-operated ignition switch

**Indicators** Digital Display: Hours, charge level, vehicle status, trouble codes

### DIMENSIONS

**Height** 44.5 in (113.3 cm)  
72 in (182.82 cm) w/ ROPS

#### W/42 in Deck

Length: 69 in (175.2 cm)  
Overall Width: 44 in (111.76 cm) w/discharge chute up  
Tire-to-tire Width: 41 in (104.14 cm)  
Tire-to-tire Width: 45 in (114.3 cm) front to back  
Weight: 783 lbs (355.16 kg)  
Weight: 814 lbs (369.22 kg) w/ROPS

### DECKS

#### Side-Discharge Decks 42"

**Type** Free-floating deck using two blades. Deck is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Construction** 11 ga, .120 in (.30 cm) welded steel with 11 ga, .120 in (.30 cm) doubler welded onto motor mount areas. Solid 1 in x .25 in (2.54 cm x .635 cm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (10.16 cm) deep which allows high-capacity mowing.

**Cutting Heights** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.18 cm to 11.43 cm).

**Mowing Blades** Heavy-duty, heat-treated, low-lift steel  
42 in: 2-20.5 in x 2.5 in x .20 in

**Blade Tip Speed** 42 in: 15,200 fpm

**Deck Drive** Each blade direct driven by electric motor.

**Discharge Chute** High density, rubberized.

**Width of Cut** 42 in: 40.4 in (103 cm)

**Trim Capacity** (left side) 42 in: 2.25 in (5.75 cm)

### ACCESSORIES

**Mulch Kit** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

#### Light Kit

**2-Bag Catcher** 5.0 bushel

**High-Performance Charger** Charge your batteries in 5.5 hours

#### Steering Extension Kit

*Specifications subject to change without notice.*

