

HUSTLER® COMMERCIAL ZERO-TURN MOWER

SUPER Z® HYPERDRIVE®

POWERHOUSE
DELIVERS UNRIValed
PERFORMANCE



INDUSTRY-LEADING PERFORMANCE AND BACKED BY INDUSTRY'S BEST WARRANTY

The Super Z® HyperDrive® features Hustler's exclusive HyperDrive transmission system - the largest, most durable drive system in the industry backed by a 3,000 hour drive system warranty. The HyperDrive also features a premium Grammer 2-way suspension seat with built-in isolator. And at up to 16 miles per hour, this zero-turn gets the job done in record time. Decreased downtime and massive increases in productivity – that's what you get from the Super Z HyperDrive.



UNRIValed PERFORMANCE
HyperDrive® industrial grade pumps and motors run all day and never break a sweat.



LEGENDARY VX4® DECK
Engineered for a 'perfect' cut every time.



INDUSTRY'S BEST WARRANTY
HyperDrive® 5-year/3000 hour pump and motor warranty.



LIMITED
WARRANTY
3 YEAR
NO
HOUR LIMIT

OR

LIMITED
WARRANTY
5 YEAR
500
HOUR

LIMITED
WARRANTY
FRAME & LEADING EDGE OF DECK
5 YEAR
3000
HOUR
PUMPS
AND
MOTORS

5 YEAR
ENGINE WARRANTY
VANGUARD ONLY

5 YEAR
3000
HOUR
PUMPS
AND
MOTORS

Find A Hustler Dealer
visit www.hustlerturf.com

ENGINE

| | |
|-----------------|--|
| Manufacturer | Vanguard |
| HP | 60", 72" deck: 36HP - BIG BLOCK™ 60", 66", 72" deck: 37HP - BIG BLOCK™ EFI (Per SAE J1995) |
| Displacement | 993cc |
| Cooling | Air cooled |
| Air Cleaner | Heavy duty canister |
| Engine Warranty | 5 year (Vanguard only) |

DRIVE SYSTEM

| | |
|--------------------|--|
| Type | Dual hydrostatic |
| Pumps | Danfoss DDC-20 |
| Wheel Motors | Parker TG280 |
| Hydraulic Lines | Stainless steel Parker seal loc technology |
| Hydraulic Cooling | Oil cooler with 9" fan |
| Reservoir Capacity | 3 gallons |
| Speed | Up to 16 mph |
| Parking Brakes | Patented automatic |

DECKS

| | |
|-------------------|---|
| Cutting Width | Side discharge: 60", 66", 72" |
| Cutting Heights | Rear discharge: 60", 72" |
| Deck Lift | 1"- 5.5" |
| Depth | Foot operated |
| Blades | 5.5" |
| Blade Length | 3 |
| | 60" deck: 3 - 20.5" x 3.0" x .25" 66" deck: 3 - 22.5" x 3.0" x .25" 72" deck: 3 - 24.5" x 3.0" x .25" |
| Spindles | Ductile cast iron with steel shafts and sealed ball bearings |
| Deck Belts | 1 |
| Drive | Electric PTO clutch |
| Construction | 7 ga. welded steel |
| Spindle Mounts | Reinforced 7 ga. spindle mount disc |
| Impact/Trim Areas | 11 ga. formed channel w/ rolled edge |

CONSTRUCTION

| | |
|---------------------|------------------------------------|
| Frame | 1.5" x 3.0" x .187" steel tubing |
| Front Caster Wheels | Mounted tapered greasable bearings |
| Front Caster Forks | Fabricated 1/2" steel |

GENERAL

| | |
|---------------|---------------------------------------|
| Seat | Grammer suspension seat with isolator |
| Fuel Capacity | 11.7 gallons |
| Cup Holder | Yes |
| Front Tire | 13 x 6.5 - 6 |
| Drive Tire | 26 x 12 - 12 |

DIMENSIONS

| | | |
|----------------------|---|----------------------------------|
| Weight | 60": 1536 lbs 66": 1551 lbs 72": 1596 lbs 72"RD: 1676 lbs | 60"RD: 1606 lbs 72": 1596 lbs |
| Height w/Rops Up | 72.5" | |
| Height w/Rops Folded | 46.8" | |
| Length | 60" deck: 89", 60"RD deck: 91.5" 66" deck: 91.5" 72", 72"RD deck: 93" | |
| Width | 60", 60"RD deck: 66" 66" deck: 72" 72", 72"RD deck: 78" | |
| Tire Width | 60", 60"RD deck: 57" 66" deck: 60" 72", 72"RD deck: 60" | |

PRODUCTIVITY*

| | |
|----------------|-------------------------------------|
| Acres Per Hour | 60": 7.76 66": 8.54 72": 9.31 |
|----------------|-------------------------------------|

OPTIONAL ACCESSORIES

| | |
|-----------------------------------|----------------|
| Semi pneumatic front tires | FlexForks® |
| Steering extension kit | Mulch kit |
| Deck rear anti-scalp wheels | Light kit |
| Electric deck lift | Sand kit |
| Flasher kit | Stripe kit |
| High vacuum deck kit | Beacon kit |
| BacVac bagger | Rear Hitch kit |
| 3-bag powered bagger (12 bushels) | |

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.

HYPERRIVE | AT A GLANCE

- VX4® deck - 7-gauge thick deck offering excellent performance in all conditions
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- HyperDrive® Hydro System – mow in tough conditions without losing performance
- HyperDrive 5-year/3000-hour pump and motor warranty
- Six-way adjustable premium Grammer suspension seat with smooth ride isolator – all day comfort
- Up to 16 mph top speed
- 13" front and 26" drive tires
- Top pinning height adjustment



Visit hustlerturf.com

and try our compare products tool!