


AL750

AL/ALT



GEHL[®]

Capacities		Metric		Imperial	
Max. height of bucket pivot point	h35	3.47 m		11 ft 4.61 in	
Max. lifting height (below forks)	h3	3.28 m		10 ft 9.13 in	
Breakout force with bucket		5906 daN		5906 daN	
Weight and dimensions					
Unladen weight (with forks) with 4-post canopy		4781 kg		10540.30 lbs	
Unladen weight (with forks)		4953 kg		10919.49 lbs	
Ground clearance	m4	0.31 m		1 ft 0.20 in	
Overall length to carriage (without hitch)	l3	4.44 m		14 ft 6.80 in	
Wheelbase	y	2.06 m		6 ft 9.10 in	
Overall width of 4 posts canopy	b22	1.45 m		4 ft 9.08 in	
Overall cab width	b4	1.45 m		4 ft 9.08 in	
Overall width (over tyres)	b1	1.74 m		5 ft 8.50 in	
Overall height with 4 posts canopy	h38	2.48 m		8 ft 1.63 in	
Overall height with cab	h17	2.48 m		8 ft 1.63 in	
Tilt-up angle	a4	45 °		45 °	
Tilt-down angle	a5	45 °		45 °	
External turning radius (over tyres)	Wa1	3.41 m		11 ft 2.25 in	
Articulation angle		45 °		45 °	
Engine					
Engine brand		Deutz		Deutz	
Engine model		TD3.6 L4		TD3.6 L4	
Number of cylinders / Capacity of cylinders		4 / 3600 cm ³		4 / 219.68 in ³	
I.C. Engine power rating / Power (kW)		74.30 Hp / 55 kW		74.30 Hp / 55 kW	
Max. torque / Engine rotation		330 Nm / 2300 rpm		330 Nm / 2300 rpm	
Engine cooling system		2 radiators water + hydraulic oil		2 radiators water + hydraulic oil	
Transmission					
Transmission type		Hydrostatic		Hydrostatic	
Number of gears (forward / reverse)		2 / 2		2 / 2	
Travel speed (laden)		30 km/h		18.64 mph	
Max. travel speed (may vary according to applicable regulations)		30 km/h		18.64 mph	
Differential lock		Machine Lock Rear & front		Machine Lock Rear & front	
Parking brake		Manual		Manual	
Hydraulics					
Hydraulic pump type		Gear pump		Gear pump	
Hydraulic flow / Pressure		69.50 l/min / 200 Bar		69.50 l/min / 2900.75 PSI	
High-Flow Option (l/min)		114.30 l/min		114.30 l/min	
Drive hydraulic system pressure		380 Bar		5511.43 PSI	
Tank capacities					
Hydraulic oil		73.80 l		19.49 US gal	
Fuel tank		102 l		26.94 US gal	
Noise and vibration					
Vibration to whole hand/arm		2.50 m/s ²		2.50 m/s ²	
Miscellaneous					
Safety cab homologation		ROPS - FOPS cab (level 1)		ROPS - FOPS cab (level 1)	



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contradictorial document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend