

AL750

ARTICULATED LOADERS



Key Features

- ✓ 4-Post Canopy ROPS and FOPS Certified
- ✓ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ✓ Inch Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Differential Lock (Hydraulically Activated Front and Rear)
- ✓ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ✓ Lift Arm with Z-Bar Kinematics, Limited Self-Level and Mechanical Return to Dig
- ✓ Lift Arm Detent
- ✓ Hydraglide™ Ride Control*
- ✓ High-Flow Auxiliary Hydraulics*

*Optional Features

Key Specifications

- ✓ 7,446 lbs (3378 kg) Static Tipping Load with Bucket Straight
- ✓ 74.4 hp (55.4 kW) gross power @ 2300 rpm
- ✓ 8' 2" (2.48 m) height to top of ROPS
- ✓ 10' 9" (3.28 m) maximum lifting height (below forks)
- ✓ 11' 2" (3.4 m) outer turning radius

SPECIFICATIONS

		METRIC
Capacities	Static tipping load with bucket (straight)	3587 kg
	Static tipping load with bucket (full turn)	2621 kg
	Max. height of bucket pivot point	3.47 m
	Max. lifting height (below forks)	3.28 m
	Breakout force with bucket	5906 daN
	Static tipping load with pallet forks - Straight with cab	2882 kg
Weight and dimensions	Unladen weight (with forks) with 4-post canopy	4781 kg
	Wheelbase	2.06 m
	Overall width of 4 posts canopy	1.45 m
	Overall cab width	1.45 m
	Overall height with 4 posts canopy	2.48 m
	Overall height with cab	2.48 m
	Tilt-up angle	45 °
	Tilt-down angle	45 °
	Articulation angle	45 °
	Overall width less bucket	1.74 m
	Overall length - Less Bucket	4.44 m
Engine	Ground clearance	0.31 m
	Engine brand	Deutz
	Engine model	TD3.6 L4
	Engine norm	Stage V
	Number of cylinders / Capacity of cylinders	4 - 3600 cm ³
	I.C. Engine power rating / Power	74.30 Hp / 55 kW
Transmission	Max. torque / Engine rotation	330 Nm / 2300 rpm
	Engine cooling system	2 radiators water + hydraulic oil
	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
Hydraulics	Max. travel speed (may vary according to applicable regulations)	30 km/h
	Travel speed (laden)	30 km/h
	Differential lock	Front and rear locking of the machine
Tank capacities	Parking brake	Manual
	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	69.50 l/min / 200 bar
	High-Flow Option (l/min)	114.30 l/min
Noise and vibration	Drive hydraulic system pressure	380 bar
	Hydraulic oil	73.80 l
	Fuel tank	102 l
Noise and vibration		< 2.50 m/s ²
Miscellaneous		ROPS - FOPS cab (level 1)



STANDARD FEATURES

- Z-Bar Loader Linkage w/ Limited Self-Leveling
- Inching Pedal
- Lift Tilt Electronic Lockout Switch
- Adjustable and telescopic steering column
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Removable Rubber Floormat
- Tilt & Lift Arm Float Detent with Detent Disable
- Two-Speed Hydrostatic Drive System
- Power-A-Tach® Attachment Mounting System
- Reverse and Brake Tail Lights
- Differential Lock
- Articulation Locking Bar
- Front and Rear - Work Lights
- Canopy
- 12Volt Power Port
- Horn
- LED work lights - On the top of the boom (fixed part) (x2)
- Cup Holder
- Seven Way Adjustable Air Suspension Seat
- Side View Mirrors
- Electronic Hand Throttle
- Oscillating Front Frame
- Adjustable arm rests

OPTIONAL FEATURES

- Back-Up Alarm
- Engine Block Heater
- LED Work Lights
- Hydraglide™ Ride Control
- 3-inch Seatbelt
- Bluetooth car radio
- High-Flow Auxiliary Hydraulics



One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.