

TH5-19

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ full size operator station
- ✓ All-in-one F-N-R joystick for machine and boom control
- ✓ Universal Skid Steer Quick Attach
- ✓ high visibility orange seat belt to verify operator use
- ✓ dedicated lift point on Quick Attach system for lifting suspended loads

Key Specifications

- ✓ 5,500 lbs. (2495 kg) maximum lifting capacity
- ✓ 19' 1" (5.8 m) maximum lifting height
- ✓ Features minimum turn radius of 10' 10" to outside tires
- ✓ 74 hp (55.4 kW) Kubota diesel engine

SPECIFICATIONS

METRIC		
Capacities	Max. capacity	2494.75 kg
	Max. lifting height	5.82 m
	Maximum outreach	3.40 m
	Breakout force with bucket	3425.13 daN
Weight and dimensions	Length to face of forks	3.89 m
	Overall width	1.81 m
	Overall height	1.92 m
	Wheelbase	2300 mm
	Ground clearance	330 mm
	Overall cab width	797 mm
	Tilt-up angle	12 °
	Tilt-down angle	117 °
	External turning radius (over tyres)	3.31 m
	Unladen weight (with forks)	4720 kg
	Tires type	Pneumatic
	Forks length / width / section	1200 mm x 125 mm x 45 mm
Performances	Lifting	8 s
	Lowering	5.40 s
	Extension	5.60 s
	Retraction	4.30 s
	Crowd	3.50 s
	Dump	3.60 s
Engine	Engine brand	Kubota
	Engine norm	Tier 4 final
	Engine model	V3307-CR-TE5B
	Number of cylinders / Capacity of cylinders	4 - 3331 cm ³
	I.C. Engine power rating - Power	74 Hp / 55.40 kW
	Max. torque / Engine rotation	1400 Nm @ 2600 rpm
	Drawbar pull	3229.40 daN
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed	25 km/h
	Max. travel speed (may vary according to applicable regulations)	25 km/h
Hydraulics	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
	Hydraulic pump type	Gear pump
Tank capacities	Hydraulic flow / Pressure	88 l/min-235 bar
	Engine oil	11.20 l
	Hydraulic oil	115 l
Miscellaneous	Fuel tank	63 l
	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Controls	Joystick



STANDARD FEATURES

- Four Wheel Drive
- Two-Speed Hydrostatic Drive System
- Back-Up Alarm
- Lockable Storage Box
- 12Volt Power Port
- Single Joystick F-N-R (JSM)
- Easy Manager
- Engine Block Heater
- Self-Leveling Forks

OPTIONAL FEATURES

- Suspension Seat
- Rearview Camera
- LED Work Lights
- Enclosed Cab with Heat and Defrost
- Air Conditioning
- Radio



One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.