

GEHL[®] DL SERIES GEN:2

TELESCOPIC HANDLERS

KEY FEATURES

- ✓ Towering Lift Heights 40-feet (13.5 m) to 55-feet (16.8 m)
- ✓ High Performance 7,000 lbs. (3175 kg) to 12,000 lbs. (5443 kg)
- ✓ 120-hp Final Tier IV Cummins Engine
- ✓ 4-Speed Powershift Transmission
- ✓ Four Wheel Drive / Four Wheel Steer
- ✓ Exceptional Visibility and Spacious Cab
- ✓ Adjustable Hydraulic System Controls to Fit the Comfort and Skill Level of the Operator





DL Series GEN:2

TELESCOPIC HANDLERS

SPECIFICATIONS

		DL7-44 GEN:2	DL9-44 GEN:2	DL11-44 GEN:2	DL11-55 GEN:2	DL12-40 GEN:2	DL12-55 GEN:2
CAPACITIES	Lift Capacity (kg)	7,000 lbs. (3176)	9,000 lbs. (4083)	11,000 lbs. (4990)	11,000 lbs. (4990)	12,000 lbs. (5444)	12,000 lbs. (5444)
	Maximum Lift Height (m)	44'4" (13.5)	44'4" (13.5)	44'4" (13.5)	55'5" (16.9)	40'4" (12.3)	55'5" (16.8)
	Capacity at Maximum Lift Height (kg)	7,000 lbs. (3176)	8,000 lbs. (3629)	8,000 lbs. (3629)	5,000 lbs. (2495)	10,000 lbs. (4536)	5,500 lbs. (2495)
	Maximum Forward Reach (m)	30'6" (9.2)	30'6" (9.2)	30'6" (9.2)	40'9" (12.2)	26'4" (8.0)	40'9" (12.2)
	Maximum Capacity at Maximum Reach (kg)	1,000 lbs. (454)	1,500 lbs. (681)	2,000 lbs. (907)	2,000 lbs. (907)	2,000 lbs. (907)	2,000 lbs. (907)
LOADER PERFORMANCE	Reach Below Grade (mm)	2'0" (610)	2'0" (610)	2'0" (610)	2'10" (864)	1'4" (406)	2'10" (864)
	Breakout Force (kN)	11,000 lbf (48.9)	12,500 lbf (55.6)	14,000 lbf (62.2)	N/A	14,000 lbf (62.2)	N/A
	Maximum Dump Height (m)	42'11" (13.1)	42'11" (13.1)	42'11" (13.1)	N/A	39'0" (11.9)	N/A
	Maximum Forward Reach at 45° Dump Angle (m)	14'3" (4.3)	14'3" (4.3)	14'3" (4.3)	N/A	11'10" (3.6)	N/A
	Dump Angle at Maximum Dump Height	24°	24°	24°	N/A	24°	N/A
	Maximum Loadover Height (m)	44'2" (13.46)	44'2" (13.46)	44'2" (13.46)	N/A	40'3" (12.3)	N/A
	Maximum Dump Height at 45° Dump Angle (m)	34'0" (10.4)	34'0" (10.4)	34'0" (10.4)	N/A	30'9" (9.4)	N/A
	Max. Forward Reach at Max. Dump Height (m)	2'3" (686)	2'3" (686)	2'3" (686)	N/A	1'2" (356)	N/A
	Rollback at Ground Level	30°	30°	30°	N/A	30°	N/A
	Total Degrees of Bucket Rotation	132°	132°	132°	N/A	132°	N/A
ENGINE	Manufacturer / Model	Cummins QSF 3.8 - Final Tier IV					
	Power (kW)	120 hp (89)					
	Aspiration	Turbocharged					
	Rated Speed	2500 rpm					
COMPONENTS	Transmission	Dana 4-Speed Power Shift					
	Maximum Travel Speed (km/hr)	22 mph (35.4)	22.8 mph (36.7)	22.8 mph (36.7)	22.8 mph (36.7)	22.8 mph (36.7)	22.8 mph (36.7)
	Steering	4-Wheel • 2-Wheel • Crab					
	Brake	Oil-Immersed, Disc-type					
	Parking Brake	Spring-Applied, Hydraulic-Released					
HYDRAULIC SYSTEM	Pump Type	Open-Center, Dual-Section					
	Total Capacity (L/min)	43 gpm (162.8)	43 gpm (162.8)	43 gpm (162.8)	43 gpm (162.8)	43 gpm (162.8)	43 gpm (162.8)
	Main Relief Pressure (bar)	3000 psi (207)	3000 psi (207)	3000 psi (207)	3000 psi (207)	3000 psi (207)	3,000 psi (207)
	Auxiliary Relief Pressure (bar)	2500 psi (172)	2500 psi (172)	2500 psi (172)	2500 psi (172)	2500 psi (172)	2,500 psi (172)
	Hydraulic Tank Capacity (L)	30 gal. (114)	30 gal. (114)	30 gal. (114)	30 gal. (114)	30 gal. (114)	62.5 gal. (237)
DIMENSIONS	Approximate Weight (kg)	23,250 lbs. (10,546)	24,650 lbs. (11,181)	25,400 lbs. (11,521)	28,460 lbs. (12,909)	25,300 lbs. (11,475)	31,840 lbs. (14,442)
	Length – Less Forks (m)	20'7" (6.3)	20'7" (6.3)	20'7" (6.3)	20'9" (6.4)	19'4" (5.9)	20'9" (6.35)
	Width (m)	8'1" (2.5)	8'3" (2.5)	8'3" (2.5)	8'3" (2.5)	8'3" (2.5)	8'3" (2.5)
	Ground Clearance (mm)	16" (400)	16" (400)	16" (400)	16" (400)	16" (400)	16" (406)
	Wheelbase (m)	10'8" (3.3)	10'8" (3.3)	10'8" (3.3)	10'8" (3.3)	10'8" (3.3)	10'8" (3.3)
	Turning Radius (m)	12'2" (3.7)	12'2" (3.7)	12'2" (3.7)	12'2" (3.7)	12'2" (3.7)	12'2" (3.7)
	Overall Height (m)	7'10" (2.3)	7'11" (2.4)	7'11" (2.4)	8'6" (2.6)	7'11" (2.4)	8'6" (2.6)
	Frame Leveling – Left / Right	10° / 10°	10° / 10°	10° / 10°	10° / 10°	10° / 10°	10° / 10°
	Fuel Capacity (L)	30 gal. (114)	30 gal. (114)	30 gal. (114)	30 gal. (114)	30 gal. (114)	30 gal. (114)
	Recommended Tire Type	13.00 x 24 G2 12-ply	14.00 x 24 G2 12-ply	14.00 x 24 G2 12-ply	14.00 x 24 G2 12-ply	14.00 x 24 G2 12-ply	14.00 x 24 G2 16-ply



GEHL COMPACT EQUIPMENT

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

GEHL
gehl.com