



M08/M100 EXCAVATORS

PREVIEW



SPECIFICATIONS

M08

M100

DRIVELINE	Engine Model	2TE67L-BV3	4TNV98CT-VBV
	Displacement	30.9 inches ³	202.5 inches ³
	Rated Speed	2,400 rpm	2,100 rpm
	Engine Output - Gross	10.3 hp	72 hp
DIMENSIONS	Transport Length	8'6"	21'4"
	Transport Height - Maximum	7'7"	9'3"
	Overall Width	2'3"	7'7"
	Tail Swing Radius	2'5"	4'4"
	Ground Level Reach - Mono Boom	8'10"	24'3"
	Dump Height - Mono Boom	6'5"	16'10"
	Dig Depth - Mono Boom	4'7"	14'10"
	Boom Swing - Left/Right	45° / 90°	60° / 60°
PERFORMANCE	Travel Speed - High/Low	1.2 mph	2.7 mph / 1.6 mph
	Dipper Breakout	1,390 lbf	9,500 lbf
	Bucket Breakout	2,360 lbf	12,216 lbf
	End Lift - Maximum Reach	529 lbs.	4,079 lbs.
	Operating Weight	2,348 lbs.	21,550 lbs.

SPECIFICATIONS ARE PRELIMINARY

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.