





## STANDARD SPECIFICATIONS

ENGINE CHOICE	250	
Туре	249.4 cc single cylinder, liquid cooled, SOHC 4-valve	
Bore & Stroke	71 x 63 mm	
EFI System / Carburetor	uretor Keihin <sup>†</sup> PTG 23	
Starting System	Electric	
Transmission	Automatic CVT, sub-transmission with forward, neutral, and reverse	
Drive Train Chain driven / solid axle		
CHASSIS		
Frame	DS 250	
Front Suspension Type / Shocks	Double A-arm 5-position adjustable pre-load	
Front Suspension Travel	5.5 in. (14 cm)	
Rear Suspension Swingarm Type / Shocks 5-position adjustable pre-load		
Rear Suspension Travel	6.7 in. (17 cm)	
Front Brake	2 hydraulic discs	
Rear Brake	1 hydraulic disc	
Tires / Front	22 x 7 x 10 in. (55.9 x 17.8 x 25.4 cm)	
Tires / Rear	20 x 11 x 9 in. (50.8 x 27.9 x 22.9 cm)	
Wheels	Steel	
DRY WEIGHT	429 lb (195 kg)	

DI	ME	ENS	INS

L x W x H (in.)	72 x 40.5 x 43.5 in.
LxWxH(cm)	183 x 103 x 110.5 cm
Wheelbase	47 in. (118.7 cm)
Seat Height	31.5 in. (80 cm)
Ground Clearance	10.2 in. (26 cm) center of ATV
Fuel Capacity	3.3 gal (12.5 L)

## **FEATURES**

Instrumentation	Neutral light, reverse light and oil / temperature light	
Lighting	2 headlamps (35-W) with tail light and brake light	
Color	Yellow	

## **WARRANTY**

Factory 6	months limited	warranty
-----------	----------------	----------



