

2015 DS 450®



STANDARD SPECIFICATIONS

ENGINE	450
Type	449.3 cc, single cylinder, liquid-cooled, DOHC 4-valve head with high-flow "Durchzugskraft" design, 38 mm intake valve, 31 mm exhaust valve Nimonic – alloy
Bore & Stroke	97 x 60.8 mm
Fuel Delivery System	46 mm Throttle Body, 16 bit / 32 MHz CPU
Starting System	Electric
Transmission	5-speed manual / heavy-duty clutch, 9 friction plates with DirectLink mechanism
Drive Train	520 O-ring high capacity chain, aluminum sprocket hub, aluminum sprocket, rigid axle

CHASSIS	
Frame	ALTEC dual-pyramidal aluminum
Front Suspension Type / Shocks	R-Type forged-aluminum Double A-arm KYB† HPG piggyback shocks with compression, rebound and preload adjustments
Front Suspension Travel	9.5 in. (24.1 cm)
Rear Suspension Type / Shocks	R-Type cast-aluminum swingarm Chromoly hollow rear axle KYB HPG piggyback shocks with compression, rebound and preload adjustments
Rear Suspension Travel	10.5 in. (26.7 cm)
Front Brakes	Dual 182 mm discs with inverted twin-piston calipers
Rear Brake	198 mm rotor with single piston caliper
Tires / Front	ITP Holeshoot† SR 21 x 7R-10 in. (53.3 x 17.8R-25.4 cm)
Tires / Rear	ITP Holeshoot SR 20 x 10R-9 in. (50.8 x 25.4R-22.9 cm)
Wheels	Polished-aluminum

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 12 to 36 months

DIMENSIONS	
Dry Weight	349 lb (158.3 kg)
L x W x H (in.)	72.4 x 46 x 41.9 in.
L x W x H (cm)	183.9 x 116.8 x 106.4 cm
Wheelbase	50 in. (126.7 cm)
Seat Height	33 in. (83.1 cm)
Ground Clearance	9 in. (22.9 cm) under frame 5.2 in. (13.2 cm) under rear axle
Fuel Capacity	3 gal (11.5 L)

FEATURES	
Instrumentation	Low fuel, check engine, neutral
Lighting	Dual removable headlights (35-W)

BEST ©2014 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. † All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am



Can-AmOffroad.com

STANDARD FEATURES

DS 450

- Rotax® 4-TEC 499.3 cc, 45.3-hp liquid-cooled engine
- 5-speed manual transmission
- KYB HPG Piggyback shocks
- R-type forged aluminum double A-arm front suspension
- R-type cast-aluminum swingarm rear suspension
- Hollow rear axle
- Inverted front brake calipers
- ALTEC dual-pyramidal aluminum frame

COLOR AND ENGINE OPTION

- Yellow / 450



PACKAGE OPTIONS

DS 450 X[®] xc

ADDED FEATURES

- R-type forged-aluminum Double A-arm with adjustable caster
- KYB HPG C36 aluminum piggyback front shocks with dual-speed compression, rebound and threaded preload adjustments and 9.6 in. (24.5 cm) of travel
- KYB HPG C40 aluminum piggyback rear shock with dual-speed compression, rebound and threaded preload adjustments and 10.5 in. (26.7 cm) of travel
- Adjustable-width hollow rear axle from 46 in. (117 cm) to 50 in. (127 cm) by increments of 0.5 in. (1.27 cm) per spacer
- Extra-strength extended 1 in. (2.54 cm) steering stem with anti-vibe mounts
- 21 x 7-10 ITP Holeshoot GNCC 6-ply front tires
- 20 x 10-9 ITP Holeshoot GNCC 6-ply rear tires
- Black-aluminum ITP 10 x 5 T-9 Trac-lock (beadlock) front wheels

- Black aluminum ITP 9 x 8 T-9 Trac-lock (beadlock) rear wheels
- 3 mm full aluminum chassis skid plate
- 5 mm full aluminum swing arm skid plate
- Aluminum nerf bars with removable aluminum heel guards
- Aluminum 6061-T6 taper-profile handlebar with square pad
- Aluminum front bumper, number plate ready
- Handlebar wind deflectors
- X-package coloration, graphics and seat cover

COLOR AND ENGINE OPTION

- Yellow & Black / 450



DS 450 X[®] mx

ADDED FEATURES

- + 2 in. Double A-arm with adjustable caster and camber give a 50 in. (127 cm) front stance
- FOX[†] FLOAT[†] X EVOL[†] front shocks with dual-speed compression and infinitely adjustable air spring and 10.7 in. (27.2 cm) of travel
- FOX PODIUM[†] X remote rear shock with dual speed compression, rebound and preload adjustments and 11.1 in. (28.2 cm) of travel
- Adjustable-width hollow rear axle from 46 in. (117 cm) to 50 in. (127 cm) by increments of 0.5 in. (1.27 cm) per spacer
- Black aluminum ITP 10 x 5 T-9 GP front wheels
- Black aluminum ITP 8 x 8 T-9 Trac-lock (beadlock) rear wheels
- 20 x 6-10 ITP QuadCross[†] MX PRO front tires

- 18 x 10 x 8 Holeshoot SR rear tires
- Extra-strength extended 1 in. (2.54 cm) steering stem with anti-vibe mounts
- Aluminum 6061-T6 taper-profile handlebar with square pad
- Aluminum front bumper, number plate ready
- Aluminum nerf bars with removable aluminum heel guards
- X-package coloration, graphics and seat cover

COLOR AND ENGINE OPTION

- Yellow & Black / 450

