

ENGINES	1000 DPS	800R	650	500 DPS
Туре	976 cc	799.9 сс	649.6 cc	499.6 cc
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)			
Bore & Stroke	91 x 75 mm	91 x 62 mm	82 x 62 mm	82 x 47 mm
Fuel Delivery System	46 mm Throttle Body, 2 Siemens† VDO injectors			
Starting System	Electric			
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking			
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok <sup>‡</sup> auto-locking front differential <sup>*</sup>			

CHASSIS				
Frame	Surrounding Spar Technology (SST) G2			
Front Suspension Type	Double A-arm			
Front Suspension Travel	9 in. (22.9 cm)			
Rear Suspension Type	Torsional Trailing arm Independent (TTI)			
Rear Suspension Travel	9.3 in. (23.6 cm)			
Front Brakes	Dual 214 mm vent	ilated disc brake	s with hydraulic t	win-piston calipers
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers			
Tires / Front	Carlisle <sup>†</sup> Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)			
Tires / Rear	Carlisle Badland 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)			
Wheels	Cast-aluminum	Steel	Steel	Cast-aluminum

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 12 to 36 months

DIMENSIONS		
Dry Weight	976 cc (DPS): 759 lb (345 kg) 799.9 cc: 729 lb (331 kg) 649.6 cc: 726 lb (329 kg) 499.6 cc (DPS): 728 lb (330 kg)	
L x W x H (in.)	86 x 46 x 49.5 in.	
L x W x H (cm)	218.4 x 116.8 x 126 cm	
Wheelbase	51 in. (129.5 cm)	
Seat Height	34.5 in. (87.7 cm)	
<b>Ground Clearance</b>	11 in. (27.9 cm)	
<b>Towing Capacity</b>	1,300 lb (590 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage	Rear: 5.7 gal (21.4 L)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES		
Instrumentation	Multifunction digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off	
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)	
Electrical	Prewired for winch	
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light	
DC Outlet	Lighter type in console, standard connector in the back (15-A)	

©2014 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. \* With Visco-Lok QE on DPS model. \* Visco-Lok is a trademark of GRN Viscobride CmbH. 7 All other trademarks are the property of their respective owners. Products are distributed in the U.S. A by DRP USInc. Because of our or riginging commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price design, features, models or equipment without incurring any obligation. Ride responsibly, BRP highly recommends that all AIV drivers lake a training course. For safety and training information, see your dealer or, in U.S. A call the AIV Safety Institute at 1.800 BR9-2687. In Canada, call the Canadian Safety Council at 1.61(3) 739-1535 et 227. AIVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protection adolften, Always remember that riding and alcohol / drugs don't mis. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.





# **OUTLANDER**

- Rotax® V-Twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok auto-locking front differential
- 230-W lighting from headlights

- High-strength, multifunction racks
- with LinQ<sup>™</sup> quick-attach accessory system 5.7-gal (21.4 L) water-resistant rear compartment
- Digitally Encoded Security System (D.E.S.S.)
- Multifunction digital gauge

### **COLOR AND ENGINE OPTIONS**

Viper Red / 800R / 650



# **OUTLANDER DPS™**

### **ADDED FEATURES**

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum wheels
- 625-W magneto

### **COLOR AND ENGINE OPTIONS**

Yellow / 1000 / 800R / 650 / 500

Light Grey / 1000 / 800R / 650 / 500



# **OUTLANDER XT™**

## **ADDED FEATURES**

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum wheels
- 26-in. Carlisle ACT radial tires
- 3,000-lb (1,361 kg) WARN<sup>†</sup> winch with roller fairlead, wired remote control and integrated remote storage
- · Heavy-duty front and rear bumpers
- Handlebar wind deflectors
- 625-W magneto
- Industry-exclusive NEXT G-1 Vista Camo color option

- Pearl White painted plastic color option
- Brushed Aluminum water dipped plastic color option

# **COLOR AND ENGINE OPTIONS**

- NEW Pearl White / 1000 / 800R / 650
- **NEW** Brushed Aluminum / 1000 / 800R / 650
- Yellow / 1000 / 800R / 650 / 500
- Camo / 1000 / 800R / 650 / 500

# **OUTLANDER XT-P**

# **ADDED FEATURES**

- Front and rear FOX† PODIUM† X Performance RC2.0 HPG Piggyback shocks
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum beadlock wheels
- 26-in. Carlisle ACT radial tires
- 3,000-lb (1,361 kg) WARN winch with roller fairlead, wired remote control and integrated remote storage
- · Heavy-duty front & rear bumpers

- · Aluminum taper-profile handlebar with wind deflectors and square pad
- Black painted plastic
- 625-W magneto
- Analog / digital gauge

## **COLOR AND ENGINE OPTIONS**

■ **NEW** Black & Orange / 1000 / 800R







# **SOUTLANDER**—GENUINE ACCESSORIES

# LINQ PREMIUM 124 L TRUNK BOX WITH REAR LIGHT

This extra large innovative Trunk Box carries up to three helmets (124 L) and has a key locking latch. It is made of heavy-duty polypropylene and has weather-resistant lid gaskets to seal out dust and moisture. The Trunk Box is offered with the LinQ system meaning it can be installed or removed in a snap, with no tools. The colored panels can also be changed to match the body color of your vehicle.

# FRONT & REAR LINQ RACK EXTENSIONS

These strong, durable Extension Racks install easily on the Outlander, thanks to the LinQ system requiring no tools. They help keep your cargo more securely in place.



The front and rear bumpers will provide additional protection against the elements. Tough and durable, they can be added on the vehicle to give your Outlander the look of an XT model.

# MUDGUARDS

It's a must to ride in the mud. Made out of injected plastic parts that perfectly fit your Outlander fenders, they offer more protection from dirt and debris.



The Deluxe Fairing provides not only wind protection, but a series of innovative features:

- Quick tool-less removal once the base brackets are mounted on the handlebar
- 2 Cup holders
- Optional GPS mounting kit
- Add-on windshield can be replaced
- Optional mirrors
- · Optional auxiliary windshield lighting

### **UNDERBELLY PROTECTION**

Aluminum plates made with high-strength 5052 H32 aluminum and plastic deflector to protect your frame from the unexpected — a must-have for rugged terrains.



# WINTER ACCESSORIES

Enjoy your Can-Am ATV all year long with our complete lineup of winter accessories such as our year-round Apache 360 track system and our wide selection of snow plows, easy to use and specially designed for your Can-Am ATV.



# **HUNTING ACCESSORIES**

When hunting season starts, you need to be ready with the right accessories specifically designed for your hunting trips such as our gun boot with mount using the LinQ system, part of the Can-Am accessories by Kolpin collection. Make sure that your camouflage is perfect with our complete choice of clothing and accessories that match your vehicle.





