

2015 OUTLANDER™ X mr



STANDARD SPECIFICATIONS

ENGINES	1000	800R	650
Type	976 cc	799.9 cc	649.6 cc
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)		
Bore & Stroke	91 x 75 mm	91 x 62 mm	82 x 62 mm
Fuel Delivery System	46 mm Throttle Body, 2 Siemens [†] VDO injectors		
Starting System	Electric		
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking		
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok [‡] QE auto-locking front differential		

CHASSIS	
Frame	Surrounding Spar Technology (SST) G2
Front Suspension Type	Double A-arm
Rear Suspension Type	Torsional Trailing arm Independent (TTI)
Front Brakes	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers
Tires / Front	30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Tires / Rear	28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Tires / Rear	30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Tires / Rear	28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	Cast-aluminum

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T available from 12 to 36 months

DIMENSIONS	1000	800R	650
L x W x H (in.)	97 x 50 x 51.5 in.	88 x 50 x 51.5 in.	88 x 46.5 x 50.5 in.
L x W x H (cm)	246 x 127 x 131 cm	224 x 127 x 131 cm	224 x 118 x 128 cm
Wheelbase	59 in. (149.9 cm)	51 in. (129.5 cm)	
Seat Height	36.75 in. (93.3 cm)		35.25 in. (89.5 cm)
Ground Clearance	13 in. (33 cm)	11.75 in. (29.9 cm)	
Towing Capacity	1,300 lb (590 kg)		
Rear Rack Capacity	200 lb (90 kg)		
Rear Storage	5.7 gal (21.4 L)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES	
Instrumentation	Multifunction digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Electrical	Prewired for winch
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)



©2014 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Drive responsibly.



Can-AmOffroad.com

PACKAGE OPTIONS

OUTLANDER 650 X mr

- 28-in. Maxxis Mudzilla[†] tires
- 12-in. cast-aluminum wheels with machined finish
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok QE
- Relocated radiator
- Heavy-duty front bumper
- Mud-riding footrests
- 625-W magneto
- X-package coloration, graphics and seat cover

COLOR AND ENGINE OPTION

- Yellow & Black / 650



OUTLANDER 800R X mr

- 30-in. Gorilla Axle Silverback[†] tires
- 14-in. ITP[†] SS312 cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- Relocated radiator
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead, wired remote control and integrated remote storage
- Heavy-duty front bumper
- Mud-riding footrests
- 625-W magneto
- X-package coloration, graphics and seat cover

COLOR AND ENGINE OPTION

- Yellow & Black / 800R



OUTLANDER 1000 X mr

- Front and rear FOX[†] PODIUM[†] X Performance RC2.0 HPG Piggyback shocks
- 30-in. Gorilla Axle Silverback tires
- 14-in. ITP SS312 cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- Relocated radiator
- 3,000-lb (1,361 kg) WARN winch with roller fairlead, wired remote control and integrated remote storage
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad

- Mudguards
- Mud-riding footrests
- 625-W magneto
- Analog / digital gauge
- 59-in. wheelbase
- Digital Camo water dipped color option
- Extra low L-gear
- X-package coloration, graphics and seat cover

COLOR AND ENGINE OPTIONS

- **NEW** Digital Camo & Manta Green / 1000
- Yellow & Black / 1000

