

2015 RENEGADE®



STANDARD SPECIFICATIONS

ENGINES	1000	800R	500
Type	976 cc	799.9 cc	499.6 cc
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)		
Bore & Stroke	91 x 75 mm	91 x 62 mm	82 x 47 mm
Fuel Delivery System	46 mm Throttle Body, 2 Siemens† VDO injectors		
Starting System	Electric		
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking		
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok‡ auto-locking front differential		

CHASSIS

Frame	Surrounding Spar Technology (SST) G2	
Front Suspension Type / Shocks	Double A-arm with FOX† HPG shocks	Double A-arm with oil shocks
Front Suspension Travel	9 in. (22.9 cm)	
Rear Suspension Type / Shocks	Torsional Trailing arm Independent (TTI) with FOX HPG shocks	Torsional Trailing arm Independent (TTI) with oil shocks
Rear Suspension Travel	9.3 in. (23.6 cm)	
Front Brakes	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear Brakes	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Tires / Front	ITP Holeshoot† ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)	
Tires / Rear	ITP Holeshoot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)	
Wheels	Cast-aluminum	

WARRANTY

Factory	6 months limited warranty
Extended	B.E.S.T. available from 12 to 36 months

DIMENSIONS

Dry Weight	976 cc: 684 lb (312 kg) 799.9 cc: 667 lb (303 kg) 499.6 cc: 614 lb (279 kg)
L x W x H (in.)	86 x 46 x 49 in.
L x W x H (cm)	218.4 x 116.8 x 124 cm
Wheelbase	51 in. (129.5 cm)
Seat Height	34.5 in. (87.7 cm)
Ground Clearance	10.5 in. (26.7 cm)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	35 lb (16 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Instrumentation	Multifunction digital gauge: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Electrical	Prewired for winch
Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)



©2014 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. † Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡ All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am®



Can-AmOffroad.com

STANDARD FEATURES

RENEGADE

- Rotax® V-Twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok auto-locking front differential
- Multifunction digital gauge
- Digitally Encoded Security System (D.E.S.S.)
- 12-in. cast-aluminum wheels
- 25-in. ITP Holeshot ATR tires
- Separate front and rear brake controls

COLOR AND ENGINE OPTIONS

■ Yellow / 1000 / 800R / 500



PACKAGE OPTION

RENEGADE X® xc

ADDED FEATURES

- Front and rear FOX PODIUM® X Performance RC2.0 HPG Piggyback shocks
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok QE
- 12-in. cast-aluminum beadlock wheels
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- 625-W magneto
- X-package coloration, graphics and seat cover
- Digital Camo water dipped color option

COLOR AND ENGINE OPTIONS

■ NEW Digital Camo & Manta Green / 1000
■ Yellow & Black / 1000 / 800R



2015 RENEGADE®—GENUINE ACCESSORIES



REAR ALUMINUM RACK
30-lb (14 kg) capacity. Compact, lightweight aluminum construction.

HEATED HAND GRIPS & THROTTLE COMBO
Ergonomically designed control module. 4 different temperature settings.



MUDGUARD KIT
Integrated extended fender flairs for sporty look and full body protection from dirt and water.

UNDERBELLY PROTECTION
Aluminum plates made with high strength 5052 H32 aluminum and plastic deflector to protect your frame from the unexpected — a must-have for rugged terrains.



HANDLEBAR WIND DEFLECTORS
Add comfort while riding with these rugged injected plastic handlebar wind deflectors.

SPORT WINDSHIELD
Offers wind protection to your Renegade without compromising its sporty look. Easy mounting system.

FRONT SHOCK COVERS
Features ventilation holes.

Shop at
store.can-am.brp.com
or at your authorized Can-Am dealer.

can-am



©2014 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.