

ENGINES	1000	650
Туре	976 cc	649.6 cc
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)	
Bore & Stroke	91 x 75 mm	82 x 62 mm
Fuel Delivery System	46 mm throttle body, 2 Siemens [†] VDO injectors	
Starting System	Electric	
Transmission	CVT, sub-transmission with high, I extra low L-gear. Sta	ow, park, neutral & reverse with an ndard engine braking
Drive Train		n with Visco-Lok [‡] QE auto-locking ferential

SST G2 6x6	
Double A-arm	
9 in. (22.9 cm)	
Double Torsional Trailing arm Independent (TTI²)	
9.3 in. (23.6 cm)	
Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Dual 214 mm ventilated disc brake with hydraulic twin-piston calipers	
Carlisle [†] ACT Radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Carlisle ACT Radial 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	
Cast-aluminum	

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 12 to 36 months

DIMENSIONS Dry Weight 976 cc: 1,135 lb (515 kg) 649.6 cc: 1,135 lb (515 kg) L x W x H (in.) 122.8 x 48.8 x 49.5 in. L x W x H (cm) 312 x 124 x 126 cm Wheelbase 82 in. (208.1 cm) Seat Height 34.5 in. (87.7 cm)
649.6 cc: 1,135 lb (515 kg) L x W x H (in.) 122.8 x 48.8 x 49.5 in. L x W x H (cm) 312 x 124 x 126 cm Wheelbase 82 in. (208.1 cm) Seat Height 34.5 in. (87.7 cm)
L x W x H (cm) 312 x 124 x 126 cm Wheelbase 82 in. (208.1 cm) Seat Height 34.5 in. (87.7 cm)
Wheelbase 82 in. (208.1 cm) Seat Height 34.5 in. (87.7 cm)
Seat Height 34.5 in. (87.7 cm)
Ground 11 in. (28 cm) Clearance
Fuel Capacity 5.4 gal (20.5 L)
Rack Capacity Front: 100 lb (45 kg) Rear: 700 lb (318 kg)
Towing Capacity 1,650 lb (750 kg)

FEATURES	
Instrumentation	Multifunction digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 6 x 6 indicator, temperature and engine lights, fuel gauge, clock, auto shut off
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Electrical	Prewired for winch
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)







OUTLANDER 6x6 XT

- Rotax® V-Twin engine options
 Continuously Variable Transmission (CVT) with extra low L-gear
- Dual-Level cargo box with modular accessories
 3,000-lb (1,361 kg) WARN† Winch with roller
- fairlead
- Double Torsional Trailing arm Independent rear suspension (TTI²)
- Tri-Mode Dynamic Power Steering (DPS™)
 1,650-lb (750 kg) towing capacity
 700-lb (318 kg) hauling capacity
 12-in. cast-aluminum wheels

- Relocated air intakes
- Heavy-duty front bumper
- Surrounding Spar Technology (SST) G2 Frame with Geometric Contact Control
- · Quick release sway bar

COLOR AND ENGINE OPTIONS

Light Grey / 650 Yellow / 1000

SS Camo / 1000





TRANSFORM INTO A FLATBED IN SECONDS



LOWER STORAGE DRY BOX AVAILABLE



TILT-ASSIST DUMPING



DUAL-STORAGE LEVELS SEPARATED BY A REMOVABLE PANEL

COUTLANDER™ 6x6 XT™—GENUINE ACCESSORIES



FULL-BODY SKID PLATE, PLASTIC

A full-body skid plate designed to protect the frame and the engine case from rough terrain conditions. The plastic allows your ATV to slide easily over stumps and logs.



HARD TOP ·····

The largest cargo box on the market (440 L) provides excellent protection. Locking secures your belongings and the usability of the cover is outstanding. Also, gas cylinders assist in raising the cover.



TAILGATE EXTENSION/DIVIDER -----

The sturdy tailgate extension provides a 25 cm extension to the cargo space. Thanks to the longer cargo bed, even large loads pose no problem. With the help of LinQ quick locks, the extension also acts as a solid space divider for the cargo bed.



LOG BARS

Allow you to convert the cargo bed into a perfect transport space for 120 cm timber. The driver's safety is guaranteed by the protective front screen.



