

ENGINES	500	450	
Туре	499.6 cc	427 cc	
	V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)	Single cylinder, liquid-cooled, SOHC, 4-valve	
Bore & Stroke	82 x 47 mm	94 x 61.5 mm	
Fuel Delivery System	46 mm Throttle Body, 2 Siemens† VDO injectors	46 mm Throttle Body, 1 Siemens† VDO injector	
Starting System	Electric		
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking		
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok <sup>‡</sup> auto-locking front differential		

CHASSIS		
Frame	Surrounding Spar Technology (SST) G2	
Front Suspension Type	Double A-arm	
Front Suspension Travel	9 in. (22.9 cm)	
Rear Suspension Type	Torsional Trailing arm Independent (TTI)	
Rear Suspension Travel	8.8 in. (22 cm)	
Front Brakes	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers	
Tires / Front	Carlisle <sup>†</sup> Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)	
Tires / Rear	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)	
Wheels	Steel Black	

WARRANTY	
Factory and	5-year warranty
Extended	(6 months limited warranty + 54 month B.E.S.T. extended warranty*)

©2014 Bombardier Recreational Products Inc (BRP). All rights reserved. M, <sup>®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. <sup>‡</sup> Visco-Lok is a trademark of KNV iscodrive GmbH. <sup>†</sup> All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all AVI drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the AIV Safety institute at 1 (300) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. AIVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs son't mix. Ever ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. AIVs with engine sizes of greater than 90c are recommended for use only by those age | 15 and older. Never canages or on any AIV or specifically designated for such use. \*Offer valid only from June 1, 2014 to January 31, 2015. **5-Year Extended Warranty**: The buyer of an eligible unit will receive the 6-month BRP Limited warranty plus 54 months B.E.S.T. extended service contract subject to a \$50 deductible on each repair. Exception for Florida residents who will receive the 60 months BRP Limited Warranty. Se your participating BRP Can-An dealer for all details and to receive a copy of the BRP Limited Warranty and B.E.S.T. and contract. The promotion is subject to termination or change at any time without notice, see website for promotion details. Manufacturer's warranty available at time of print. REVISED MAY 6, 2014

DIMENSIONS	
Dry Weight	499.6 cc: 740 lb (336 kg) 427 cc: 715 lb (324 kg)
L x W x H (in.)	91 x 46 x 52.5 in.
L x W x H (cm)	231 x 116.8 x 133 cm
Wheelbase	59 in. (149.9 cm)
Seat Height	33.8 in. (85.8 cm)
Ground Clearance	10.5 in. (26.7 cm)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage	Rear: 2.9 gal (10.9 L)
Fuel Capacity	5.4 gal (20.5 L)
EEATHDEC	

FEATURES	
Instrumentation	Multifunction digital gauge: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Electrical	Prewired for winch
Lighting	70-W from dual 35-W front light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)



## **OUTLANDER L MAX**

- Rotax® engine options
   Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspensionTorsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok auto-locking front differential
  1,300-lb (590 kg) towing capacity
  5.4-gal (20.5 L) fuel capacity
  25-in. Carlisle Trail Wolf tires

- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge

- Steel racks with LinQ<sup>™</sup> quick-attach accessory system and a combined 360 pound (163.3 kg) capacity
   2.9-gal (10.9 L) water-resistant rear compartment
- Dynamic passenger comfort ergonomics
  Mulitiposition passenger handgrips
- Raised floorboards
- 5-year promotional warranty

### **COLOR AND ENGINE OPTIONS**

Viper Red / 500 / 450



# **OUTLANDER L MAX DPS**

### **ADDED FEATURES**

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum wheels
- 500-W magneto

### **COLOR AND ENGINE OPTIONS**

- Yellow / 500 / 450
- Light Grey / 500 / 450









**MULTIFUNCTION DIGITAL GAUGE** 




2.9-GAL (10 L) WATER-RESISTANT REAR COMPARTMENT

### **GUN BOOT† 6.0 IMPACT† BY KOLPIN† AND GUN BOOT RACK**

- Features largest interior room of all Kolpin Gun Boot cases.
- · Extra room for pistol-grip-type weapons and small bipods.





- · Easy and fast to install and remove from racks.
- Flip-over cover with quick-release hinge pins makes it easy to remove.

### **SOFT STORAGE BAG**

- 3-section bag.
- Transport gear in a waterproof bag.
- 6" tall soft cargo bag for the Outlander front or back racks.
- Designed with Outlander racks & rack extensions to maximize potential storage.



