

2015 OUTLANDER™ L



Outlander L DPS accessorized unit shown

STANDARD SPECIFICATIONS

ENGINES	500	450
Type	499.6 cc V-twin, liquid-cooled, SOHC, 8-valve (4-valve / cyl)	427 cc Single cylinder, liquid-cooled, SOHC, 4-valve
Bore & Stroke	82 x 47 mm	94 x 61.5 mm
Fuel Delivery System	46 mm Throttle Body, 2 Siemens [†] VDO injectors	46 mm Throttle Body, 1 Siemens [†] VDO injector
Starting System	Electric	
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking	
Drive Train	Selectable 2WD / 4WD shaft driven with Visco-Lok [‡] auto-locking front differential	

CHASSIS

Frame	Surrounding Spar Technology (SST) G2
Front Suspension Type	Double A-arm
Front Suspension Travel	9 in. (22.9 cm)
Rear Suspension Type	Torsional Trailing arm Independent (TTI)
Rear Suspension Travel	8.8 in. (22 cm)
Front Brakes	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear Brake	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers
Tires / Front	Carlisle [‡] Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Tires / Rear	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	Steel Black

WARRANTY

Factory and Extended 5-year warranty
(6 months limited warranty + 54 month B.E.S.T. extended warranty*)

BEST PROTECTION ©2014 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. † Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡ All other trademarks are the property of their respective owners. Products are distributed in the U.S.A. by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. *Offer valid only from June 1, 2014 to January 31, 2015. 5-Year Extended Warranty: The buyer of an eligible unit will receive the 6-month BRP Limited warranty plus 54 months B.E.S.T. extended service contract subject to a \$50 deductible on each repair. Exception for Florida residents who will receive the 60 months BRP Limited Warranty. See your participating BRP Can-Am dealer for all details and to receive a copy of the BRP Limited Warranty and B.E.S.T. contract. The promotion is subject to termination or change at any time without notice, see website for promotion details. Manufacturer's warranty available at time of print.

REVISED MAY 6, 2014

DIMENSIONS

Dry Weight	499.6 cc: 703 lb (319 kg) 427 cc: 678 lb (308 kg)
L x W x H (in.)	83 x 46 x 49 in.
L x W x H (cm)	211 x 116.8 x 124 cm
Wheelbase	51 in. (129.5 cm)
Seat Height	33.8 in. (85.8 cm)
Ground Clearance	10.5 in. (26.7 cm)
Towing Capacity	1,300 lb (590 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage	Rear: 2.9 gal (10.9 L)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Instrumentation	Multifunction digital gauge: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock, auto shut off
Electrical	Prewired for winch
Lighting	70-W from dual 35-W front light / brake light
DC Outlet	Lighter type in console, standard connector in the back (15-A)

can-am



Can-AmOffroad.com

STANDARD FEATURES

OUTLANDER L

- Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspension
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok auto-locking front differential
- 1,300-lb (590 kg) towing capacity
- 5.4-gal (20.5 L) fuel capacity
- 25-in. Carlisle Trail Wolf tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge

- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment
- 5-year promotional warranty

COLOR AND ENGINE OPTIONS

- Viper Red / 500 / 450
- Light Grey / 500 / 450



PACKAGE OPTION

OUTLANDER L DPS™

ADDED FEATURES

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok QE
- 12-in. cast-aluminum wheels
- 500-W magneto
- Industry-exclusive NEXT G-1 Vista Camo color option

COLOR AND ENGINE OPTIONS

- Yellow / 500 / 450
- Light Grey / 500 / 450
- Camo / 500 / 450



HIGHLIGHTS



MULTIFUNCTION DIGITAL GAUGE



2.9-GAL (10 L) WATER-RESISTANT REAR COMPARTMENT

2015 OUTLANDER™ L—GENUINE ACCESSORIES

HEAVY-DUTY BASKET

- Made of high-strength, low-alloy steel.
- LinQ Mounted, with toe-in makes it easy to install and remove. Can be placed on both front and back racks of vehicle.



SOFT STORAGE BAG

- 3-section bag.
- Transports gear in a waterproof bag.
- 6" tall soft cargo bag for the Outlander front or back rack.
- Designed with Outlander racks and rack extensions to maximize potential storage.

HIGH WINDSHIELD KIT

- Provides excellent wind protection.
- Fits straight and tapered handlebars.
- Easy mounting system allows you to install it effortlessly.

XT REAR BUMPER

- Large tube construction.
- Protects vehicle frame against the obstacles.



RACK EXTENSION — LOW & HIGH

- Made of carbon steel.
- Provides tie-down points to secure cargo on racks.
- Easy installation on tubular rack.

XT FRONT BUMPER

- Large tube construction.
- Protects vehicle frame against the obstacles.
- Winch compatible.

CAN-AM TERRA 25 BY SUPERWINCH

Pulling strength capability of 2,500 lbs (1,134 kg).

Shop at
store.can-am.brp.com
or at your authorized Can-Am dealer.

can-am

