≋COMMANDER[™] DPS[™]

HIGHLIGHTS

- Rotax[®] V-twin engine options
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok[‡] QE auto-locking front differential
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear ٠ suspension (TTI) with external sway bar
- Intelligent Throttle Control (iTC[™])
 Industry's exclusive Dual-Level[™] cargo box
- 14-in. cast-aluminum wheels with ٠ 27-in. Maxxis Bighorn 2.0⁺ tires
- · Adjustable driver's seat and tilt steering



ENGINE	800R	1000	
Туре	71 hp, Rotax 799.9 cc, V-twin, liquid cooled	85 hp, Rotax 976 cc, V-twin, liquid cooled	
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)		
Transmission	CVT, L / H / N / R / P, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Double A-arm with dive-control geometry 10 in. (25.4 cm) travel		
Front Shocks	Motion Control		
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) with external sway bar 10 in. (25.4 cm) travel		
Rear Shocks	Motion Control		
BRAKES			

Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS		
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)	
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)	
Wheels	14 in. cast aluminum	

DIMENSIONS / CAPACITIES		
LxWxH	118.3 x 58.6 x 72 in. (300.4 x 148.9 x 182.9 cm)	
Wheelbase	75.8 in. (192.4 cm)	
Ground Clearance	11 in. (27.9 cm)	
Dry Weight*	1,287 lb (584 kg)	
Rack Capacity	600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg)	
Storage Capacity	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)	
Towing Capacity	1,500 lb (680 kg)	
Fuel Capacity	10 gal (37.8 L)	

Multifunction Digital: Speedometer, tachometer, dometer, trip and hour	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)	
seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Lighting	240-W from four 60-W projectors with tail lights / brake lights	
Prewired for winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)	
N/A			
	Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO [™] mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off Prewired for winch	Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off Prewired for winch Anti-theft System	

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months

Front Rear

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. ^{TM, ®} and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GKN Viscodrive GmbH. "All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Head the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs on't mix. SSV is for off-road use only. Never ride on paved suffaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

