

# 2016 COMMANDER™ XT-P™

## HIGHLIGHTS

- Rotax® V-twin engine
- Tri-Mode Dynamic Power Steering (DPS™)
- Intelligent Throttle Control (iTC™)
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI) with external sway bar
- Front and rear FOX<sup>†</sup> 2.0 PODIUM<sup>†</sup> RC2 shocks
- Front sway bar
- Industry's exclusive Dual-Level™ cargo box
- 12-in. aluminum beadlock wheels with 27-in. Maxxis Bighorn 2.0<sup>†</sup> tires
- WARN<sup>†</sup> winch
- Heavy-duty front bumper
- Mudguards
- Rock sliders
- Analog / Digital gauge



■ Black & Orange / 1000

ENGINE	1000
Type	85 hp, Rotax 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, L / H / N / R / P, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with dive-control geometry with external front sway bar 10 in. (25.4 cm) travel
Front Shocks	FOX 2.0 PODIUM RC2 Piggyback
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) with external sway bar 10 in. (25.4 cm) travel
Rear Shocks	FOX 2.0 PODIUM RC2 Piggyback

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	4,500-lb (2,041 kg) WARN winch with roller fairlead	Lighting	240-W from four 60-W projectors with tail lights / brake lights
Protection	Heavy-duty front bumper, mudguards, rock sliders	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months

TIRES / WHEELS	
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)
Wheels	12 in. aluminum beadlock

DIMENSIONS / CAPACITIES	
L x W x H	120.2 x 62.5 x 72 in. (305.3 x 158.7 x 182.9 cm)
Wheelbase	75.8 in. (192.4 cm)
Ground Clearance	11 in. (27.9 cm)
Dry Weight*	1,287 lb (584 kg)
Rack Capacity	600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg)
Storage Capacity	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	1,500 lb (680 kg)
Fuel Capacity	10 gal (37.8 L)

**BEST** ©2015 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodriv GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



Can-AmOffroad.com

