## amaverick max dps and the second sec

## **HIGHLIGHTS**

- 101-hp Rotax® 1000R V-twin engine with high-flow dynamics
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with Zylon<sup>†</sup>-reinforced belt
- · Mid-engine layout for mass centralization
- Double A-arm front suspension with 14 in. (35.6 cm) of travel
- Torsional Trailing A-arms independent rear suspension (TTA) with 14 in. (35.6 cm) of travel
- Front and rear FOX<sup>†</sup> 2.0 PODIUM<sup>†</sup> C shocks

- 12-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0<sup>†</sup> tires
- High-strength, 150-lb (68 kg) multipurpose rear rack with LinQ<sup>™</sup> quick-attach system
- · Adjustable driver's seat and tilt steering
- · Passenger handhold and grab bar



ENGINE	1000R
Туре	101 hp, Rotax 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine brake
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 14 in. (35.6 cm) travel
Front Shocks	FOX 2.0 PODIUM C Piggyback with compression and preload adjustments
Rear Suspension	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar 14 in. (35.6 cm) travel
Rear Shocks	FOX 2.0 PODIUM C Piggyback with compression and preload adjustments

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic single-piston caliper

TIRES / WHEELS			
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm)		
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm)		
Wheels	12 in. cast aluminum		

DIMENSIONS / CAPACITIES		
LxWxH	148 x 64 x 78 in. (376 x 162.5 x 198 cm)	
Wheelbase	113.8 in. (289.1 cm)	
Ground Clearance	12.5 in. (31.75 cm)	
Dry Weight	1,563 lb (708.9 kg)	
Rack Capacity	150 lb (68 kg) with LinQ quick-attach	
Storage Capacity	Glove box: 4.5 gal (17.2 L) Center console: 0.3 gal (1.3 L)	
Towing Capacity	N/A	
Fuel Capacity	10 gal (37.8 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	N/A
		Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240-W from four 60-W projectors with tail lights / brake lights
Winch	Prewired for winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



