

# 2016 MAVERICK™ X® mr

## HIGHLIGHTS

- 101-hp Rotax® 1000R V-twin engine with high-flow dynamics
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok† QE auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with Zylon†-reinforced belt
- Extra low L-gear
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms independent rear suspension (TTA) with 12 in. (30.5 cm) of travel
- Front and rear FOX† 2.5 PODIUM† RC2 Piggyback shocks
- 14-in. ITP† SS312 cast-aluminum wheels with 30-in. Gorilla Axle Silverback† tires
- Strategically positioned engine air intake and CVT inlets / outlets
- WARN† winch
- Analog / Digital gauge
- Adjustable driver's seat and tilt steering
- Passenger handhold and grab bar
- X-package seat trims, graphics and sponsor decals



- Digital Camo & Manta Green / 1000R
- White, Black & Can-Am Red / 1000R
- Hyper Silver, Black & Octane Blue / 1000R

ENGINE	1000R
Type	101 hp, Rotax 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine brake
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Front Suspension	Double A-arm 12-in. (30.5 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and preload adjustments
Rear Suspension	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar 12-in. (30.5 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and preload adjustments

## BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers

## FEATURES

Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	N/A
Winch	4,500-lb (2,041 kg) WARN winch with roller fairlead	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240-W from four 60-W projectors with tail lights / brake lights
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

## WARRANTY

Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months

TIRES / WHEELS	
Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Wheels	14 in. ITP SS312 cast aluminum

## DIMENSIONS / CAPACITIES

L x W x H	118.8 x 67.9 x 76.2 in. (302 x 172 x 194 cm)
Wheelbase	84.3 in. (214.1 cm)
Ground Clearance	15 in. (38 cm)
Dry Weight*	1,297 lb (588 kg)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	N/A
Fuel Capacity	10 gal (37.8 L)

**BEST** ©2015 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodriv GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

**can-am**



Can-AmOffroad.com