©OUTLANDER DPS™

HIGHLIGHTS

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok[‡] QE auto-locking front differential
- 12-in. cast-aluminum wheels
- · 230-W lighting from headlights
- 625-W magneto

- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- Digitally Encoded Security System (D.E.S.S.™)
- Multifunction digital gauge



Viper Red / 5/0
Light Grey / 570 / 650 / 850 / 1000R

ENGINES	570	650	850	1000R
Туре	48 hp, Rotax 570 cc V-twin, liquid cooled	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)			
Transmission	CVT, P / R / N / H / L, standard engine braking			
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential			
Power Steering	Tri-Mode Dynamic Power Steering (DPS)			

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEE	LS
Front Tires	Carlisle [†] Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Badland 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES		
LxWxH	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	570 / 729 lb (330 kg) 650 / 726 lb (329 kg) 850 / 730 lb (331 kg) 1000R / 767 lb (348 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	N/A
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
Protection	N/A		

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



