©OUTLANDER™ MAX DPS™

HIGHLIGHTS

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels
- Convertible Rack System (CRS) with LinQ[™] system
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards

- High-strength, multipurpose racks with LinQ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- 625-W magneto



ENGINES	570	650
Туре	48 hp, Rotax 570 cc V-twin, liquid cooled	62 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS	S
Front Tires	Carlisle [†] Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Badland 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES	
LxWxH	94 x 46 x 53 in. (238.8 x 116.8 x 135 cm)
Wheelbase	· · · · · · · · · · · · · · · · · · ·
Mileelpase	59 in. (149.9 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	570 / 793 lb (359 kg)
	650 / 795 lb (361 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
	Meai: 200 ib (30 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Seat	Convertible Rack System (CRS)
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Protection	N/A		

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



