SOUTLANDER™ MAX LIMITED

IGHLIGHTS

- Rotax® V-twin engine
- Rear Air Control Suspension (ACS) with FOX[†] Air Assist shocks
- Continuously Variable Transmission (CVT) ٠ with engine braking Tri-Mode Dynamic Power Steering (DPS[™])
- •
- Garmin[†] Montana[†] 650t touchscreen GPS •
- 3,000-lb (1,361 kg) WARN[†] winch • with roller fairlead
- Heavy-duty front and rear bumpers
- 12-in. cast-aluminum wheels with LIMITED finish
- 26-in. Carlisle[†] ACT radial tires

- · Handlebar wind deflectors
- Multifunction Analog / Digital gauge
- Mudguards
- Comfort grips
- Painted plastics



1000R
89 hp, Rotax 976 cc V-twin, liquid cooled
Electronic Fuel Injection (EFI)
CVT, P / R / N / H / L, standard engine braking
Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential
Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	Air Control Suspension (ACS) with FOX Air Assist
BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS				
Front Tires	Carlisle ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)			
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)			
Wheels	12 in. cast-aluminum with LIMITED finish			

DIMENSIONS / CAPACITIES		
LxWxH	94 x 46 x 53 in. (238.8 x 116.8 x 135 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Dry Weight*	824 lb (374 kg)	
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Integrated / removable Garmin Montana 650t touchscreen GPS, Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Seat	Convertible Rack System (CRS)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors, mudguards	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



Rear

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. [®]Base model dry weight shown. ^{TV}Isco-Lok is a trademark of GKU Viscodrive GmbH. ^YAll other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change sectifications, price, design, features, models or equipment without incurring any polyligation. Rife responsibly, BRP high vecommends that all AV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate.** For your safety: the operator and passenger should wear a helmet, eye protection and other protective clubing. Always remember that riding and alcohol / drugs don't this. Avere ride on parties of public trads. Never engage in studi wear a helmet, eye protection and publication Ride redefined on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com