## **©OUTLANDER™ MAX XT-P™**

## PACKAGE HIGHLIGHTS

- Rotax® V-twin engine options
- Front and rear FOX<sup>†</sup> Performance Series 1.5 PODIUM<sup>†</sup> RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN<sup>†</sup> winch with roller fairlead
- · Heavy-duty front and rear bumpers
- 12-in. cast-aluminum beadlock wheels
- 26-in. Carlisle† ACT radial tires
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Multifunction Analog / Digital gauge

- Convertible Rack System (CRS) with LinQ<sup>™</sup> system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Black painted plastic



Black & Orange / 850 / 1000R

<b>ROTAX ENGINES</b>	850	1000R			
Туре	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled			
Fuel Delivery System	Electronic Fuel Injection (EFI)				
Transmission	CVT, P / R / N / H / L, standard engine braking				
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential				
Power Steering	Tri-Mode Dynamic Power Steering (DPS)				

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX Performance Series 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX Performance Series 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS			
Front Tires	Carlisle ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)		
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)		
Wheels	12-in. cast-aluminum beadlock		

DIMENSIONS / CAPACITIES			
LxWxH	94 x 46 x 53 in. (238.8 x 116.8 x 135 cm)		
Wheelbase	59 in. (149.9 cm)		
Ground Clearance	11 in. (27.9 cm)		
Seat Height	34.5 in. (87.7 cm)		
Engine / Dry Weight*	850 / 797 lb (361 kg) 1000R / 824 lb (374 kg)		
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	1,300 lb (590 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES	
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad

Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Seat	Convertible Rack System (CRS)
Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

	# . W	-		7. W	ч .	 w.
- TAT	7 A W	- 1	-	Al	M	V*/
	/ <del>-</del> 1	A W	A		N 1	

Factory	6 months limited warranty		
Extended	B.E.S.T. available from 6 to 30 months		





