\mathbb{\mathbb{G}OUTLANDER\mathbb{\mathbb{K}} X\mathbb{\mathbb{R}} mr 1000R

IGHLIGHTS

- Rotax® V-twin engine
- Front and rear FOX[†] Performance Series 1.5 PODIUM† RC2 shocks
- 30-in. Gorilla Axle Silverback† tires
- 14-in. ITP[†] SS312 cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Relocated radiator
- 3,000-lb (1,361 kg) WARN † winch with roller fairlead
- · Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Mudguards
- · Mud-riding footrests

- 59-in. wheelbase
- Multifunction Analog / Digital gauge
- X-package coloration, graphics and seat cover



White, Black & Can-Am Red / 1000R 🍱 Digital Camo & Manta Green / 1000R

ENGINE	1000R
Туре	89 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm
Front Shocks	FOX Performance Series 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI)
Rear Shocks	FOX Performance Series 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS		
Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)	
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)	
Wheels	14 in. ITP SS312 cast aluminum	

DIMENSIONS / CAPACITIES		
LxWxH	97 x 50 x 51.5 in. (246 x 127 x 131 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	13 in. (33 cm)	
Seat Height	36.75 in. (93.3 cm)	
Dry Weight	990 lb (449 kg)	
Rack Capacity	Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	N/A
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad, mud-riding footrests and mudguards		

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



