# agoutlander X° mr 650

### HIGHLIGHTS

- Rotax® V-twin engine
- 28-in. Maxxis Mudzilla<sup>†</sup> tires
- 12-in. cast-aluminum wheels with machined finish
- Tri-Mode Dynamic Power Steering (DPS<sup>™</sup>)
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Relocated radiator •
- Heavy-duty front bumper •
- Mud-riding footrests •
- Surrounding Spar Technology (SST) G2 frame • with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry

- Torsional Trailing arm Independent rear suspension (TTI)
- 625-W magneto
- X-package coloration, graphics and seat cover



White, Black & Can-Am Red / 650

ENGINE	650
Туре	62 hp, Rotax 649.6 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI)
Rear Shocks	Oil

## RRAKES

Rear

## Front

Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

<b>TIRES / WHEELS</b>	
Front Tires	Maxxis Mudzilla 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	Maxxis Mudzilla 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES		
LxWxH	88 x 46.5 x 50.5 in. (224 x 118 x 128 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	11.75 in. (29.9 cm)	
Seat Height	35.25 in. (89.5 cm)	
Dry Weight	874 lb (396 kg)	
Rack Capacity	Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

### FFATURE

Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connecto in the back (15-A)
		Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	N/A
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front bumper, mud-riding footrests		

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>TM</sup>, <sup>®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. "Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate. For your safety:** the operator and passenger should wear a helmet, eye protection and other protective clothing. *Always* The careful of difficult terain. Alves with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never cary passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com