SOUTLANDER™ XT-P™

HIGHLIGHTS

- Rotax[®] V-twin engine options
- Front and rear FOX⁺ Performance Series 1.5 PODIUM[†] RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS[™]) 3,000-Ib (1,361 kg) WARN[†] winch
- with roller fairlead
- 12-in. cast-aluminum beadlock wheels ٠
- 26-in. Carlisle[†] ACT radial tires
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- 625-W magneto

- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- Multifunction Analog / Digital gauge
- · Black painted plastic



Black & Orange / 850 / 1000R

ENGINES	<mark>850</mark>	1000R
Туре	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX Performance Series 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX Performance Series 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS		
Front Tires	Carlisle ACT radial	
	26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle ACT radial	
	26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	
Wheels	12-in. cast-aluminum beadlock	

DIMENSIONS / CAPACITIES	
LxWxH	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	850 / 730 lb (331 kg) 1000R / 767 lb (348 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter,	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
	4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Seat	N/A
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S)
Protection	Heavy-duty front & rear bumpers, aluminum taper- profile handlebar with wind deflectors and square pad		

WARRANTY	
Factory	6 months limited warranty
Extended B.E.S.T. available from 6 to 30 months	



©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [©] and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. [®]Base model dry weight shown. ^{TV}Isco-Lok is a trademark of GKU Viscodrive GmbH. ^YAll other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change sectifications, price, design, features, models or equipment without incurring any polyligation. Rife responsibly, BRP high vecommends that all AV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate.** For your safety: the operator and passenger should wear a helmet, eye protection and other protective clubing. Always remember that riding and alcohol / drugs don't this. Avere ride on parties of public trads. Never engage in studi wear a helmet, eye protection and publication Ride redefined on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com