# areas and a second seco

# HIGHLIGHTS

- Rotax<sup>®</sup> V-twin engine options
- Front and rear FOX<sup>+</sup> Performance Series 1.5 PODIUM<sup>†</sup> RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS<sup>™</sup>) •
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshot  $^{\dagger}$  ATR tires •
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind ٠ deflectors and square pad
- Surrounding Spar Technology (SST) G2 frame • with Geometric Contact Control
- Double A-arm front suspension with ٠ dive-control geometry

- Torsional Trailing arm Independent ٠ rear suspension (TTI)
- ٠ Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Multifunction digital gauge ٠
- X-package coloration, graphics • and seat cover



White, Black & Can-Am Red / 850 / 1000R 🗾 Digital Camo & Manta Green / 1000R

ENGINES	850	1000R
Туре	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, st	andard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lo	ok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

#### SUSPENSIO

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX Performance Series 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX Performance Series 1.5 PODIUM RC2

Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES	
LxWxH	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	850 / 668 lb (303 kg) 1000R / 692 lb (314 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

### FEATURES

BRAKES

Front Rear

Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock
Prewired for available winch
Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, aluminum skid plate

Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Seat	N/A
Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

## VARRANT\

WARNANTI	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months



©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>TM</sup>, <sup>®</sup> and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. <sup>®</sup>Base model dry weight shown. <sup>TV</sup>Isco-Lok is a trademark of GKU Viscodrive GmbH. <sup>Y</sup>AII other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change sectifications, price, design, features, models or equipment without incurring any polyligation. Rife responsibly, BRP high vecommends that all AV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227. **ATVs can be hazardous to operate.** For your safety: the operator and passenger should wear a helmet, eye protection and other protective clubing. Always remember that riding and alcohol / drugs don't this. Avere ride on parties of public trads. Never engage in studi wear a helmet, eye protection and publication Ride redefined on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



Can-AmOffroad.com