## **RENEGADE**

## **HIGHLIGHTS**

- Rotax® V-twin engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™) (850 and 1000R)
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent rear suspension (TTI)
- Visco-Lok<sup>‡</sup> QE auto-locking front differential
- Multifunction digital gauge
- Digitally Encoded Security System (D.E.S.S.™)

- 12-in. cast-aluminum wheels
- 25-in. ITP Holeshot† ATR tires
- Separate front and rear brake controls



Can-Am Red / 570 / 850 / 1000R

ENGINES	570	850	1000R
Туре	48 hp, Rotax 570 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential	o-Lok Selectable 2WD / 4WD with Visco-Lok QE front auto-locking front differential	
Power Steering	N/A	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS		
Front Suspension		Double A-arm 9 in. (22.9 cm) travel
Front Shocks	0il	FOX† HPG
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel	
Rear Shocks	Oil	FOX HPG

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEEL	S
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES		
LxWxH	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)	
Wheelbase	51 in. (129.5 cm)	
Ground Clearance	10.5 in. (26.7 cm)	
Seat Height	34.5 in. (87.7 cm)	
Engine / Dry Weight*	570 / 615 lb (279 kg) 850 / 668 lb (303 kg) 1000R / 692 lb (314 kg)	
Rack Capacity	Rear: 35 lb (16 kg)	
Storage Capacity	N/A	
Towing Capacity	1,300 lb (590 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights,	Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
	fuel gauge, clock	Seat	N/A
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
Protection	Front bumper, optional wind deflectors		

WARRANTY	
Factory	6 months limited warranty
Extended	B.E.S.T. available from 6 to 30 months





