BDEFENDER XT■ The state of the state of

HIGHLIGHTS

- Heavy-duty Rotax® V-Twin engine options
- PRO-TORQ transmission
- Dynamic Power Steering (DPS™)
- Lockable rear differential and Visco-Lok[‡] QE auto-locking front differential
- TTA-HD rear suspension
- 14-in. (35.6 cm) black cast-aluminum wheels with 27-in. (68.6 cm) Maxxis Bighorn 2.0[†] tires
- ECO™ / Work / Normal driving modes
- 16.2 gal (61.3 L) of storage capacity including a 1.7-gal (6.3 L) water-resistant toolbox and a 5.6-gal (21 L) waterproof under passenger seat storage box
- VERSA-PRO bench seat with reinforced XT seat skin and adjustable driver seat
- Multifunction cargo box with sturdy tailgate
- 4,500-lb (2,014 kg) winch
- Full hard roof
- · Full skid plate
- Multifunction analog / digital gauge
- 1-year maintenance free and easy access to key maintenance components
- Painted color options and Mossy Oak[†] Break-Up Country Camo[†] water dipped option



Pure Magnesium Metallic / HD8 / HD10

Intense Red / HD8 / HD10

Mossy Oak Break-Up Country Camo / HD8 / HD10

ENGINES	HD8	HD10
Туре	50 hp, Rotax 799.9 cc, V-twin, liquid cooled	72 hp, Rotax 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™)	with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P	
Drive Train	True 4-mode traction system: 2x4 open rear dif., 2x4 locked rear dif., 4x4 open rear dif., 4x4 locked rear dif. Visco-Lok QE auto-locking front dif.	
Driving Assistance	Electronic Hill Descent Control ECO / Work / Normal modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS	
Front Suspension	Double A-arm / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA-HD with external sway bar / 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks
Rear Shocks	Twin tube gas charged shocks

BRAKES		
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers	

TIRES / WHEELS	S
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14-in. black cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	120 x 62 x 78 in. (305 x 157.5 x 198.1 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	11 in. (28 cm)
Estimated Dry Weight	1,550 lb (703 kg)
Cage	ROPS-approved profiled cage. Certified ISO 3471 and OSHA.
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.2 gal (61.3 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 0.9 gal (3.5 L)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO / Work / Normal modes, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Lighting	140-W lighting output from four 35-W reflectors ensuring a wide visiblity, plus LED tail lights with halo glow effect
		Winch	4,500-lb (2,041 kg) winch with roller fairlead
		Seat	VERSA-PRO bench seat with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced XT seat skin and contoured bench to improve entrance/exit of the cab
Battery	12 V (30 amp/h)	Protection	Integrated front steel bumper, full skid plate, full hard roof
Magneto	650 W	Hitch Type	2-in. hitch receiver
Instrumentation	Two lighter type DC outlets, one in the console (20-A) and one in the under dash storage (20-A)	Steering Wheel	Adjustable tilt steering

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage





