

2017 MAVERICK™ xc DPS™

HIGHLIGHTS

- 101-hp Rotax® 1000R V-twin engine with high-flow dynamics
- 60-in. (152.4 cm) overall width
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok⁺ QE auto-locking front differential
- Intelligent Throttle Control (iT^{CM})
- Continuously Variable Transmission (CVT) with Zylon⁺-reinforced belt
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms (TTA) independent rear suspension with 12 in. (30.5 cm) of travel
- Front sway bar
- Front and rear FOX⁺ 2.0 PODIUM⁺ C shocks
- 12-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0⁺ tires
- High-strength, 200-lb (91 kg) multipurpose rear rack with LinQ™ quick-attach system
- Adjustable driver's seat and tilt steering
- Passenger handhold and grab bar



White / 1000R

ENGINE

1000R

| | |
|----------------------|---|
| Type | 101 hp, Rotax 976 cc, V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iT ^{CM}) with Electronic Fuel Injection (EFI) |
| Transmission | CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine brake |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Double A-arm with sway bar 12 in. (30.5 cm) travel |
| Front Shocks | FOX 2.0 PODIUM C Piggyback with compression adjustment |
| Rear Suspension | Torsional Trailing A-arms (TTA) independent with sway bar 12 in. (30.5 cm) travel |
| Rear Shocks | FOX 2.0 PODIUM C Piggyback with compression adjustment |

BRAKES

| | |
|-------|--|
| Front | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers |

TIRES / WHEELS

| | |
|-------------|---|
| Front Tires | Maxxis Bighorn 2.0 27 x 9 x 12 in. (68.6 x 22.9 x 30.5 cm) |
| Rear Tires | Maxxis Bighorn 2.0 27 x 11 x 12 in. (68.6 x 27.9 x 30.5 cm) |
| Wheels | 12-in. cast-aluminum |

DIMENSIONS / CAPACITIES

| | |
|------------------|---|
| L x W x H | 118.8 x 60 x 72.2 in. (301.7 x 152.4 x 183.4 cm) |
| Wheelbase | 84.3 in. (214.1 cm) |
| Ground Clearance | 11 in. (28 cm) |
| Dry Weight* | 1,290.8 lb (585 kg) |
| Rack Capacity | 200 lb (91 kg) with LinQ quick-attach |
| Storage Capacity | Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L) |
| Towing Capacity | N/A |
| Fuel Capacity | 10 gal (37.8 L) |

FEATURES

| | | | |
|-------|---|-------------------|--|
| Gauge | Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off | Protection | N/A |
| Winch | Prewired for winch | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | | Lighting | 240 W from four 60-W projectors with tail lights / brake lights |
| | | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |

WARRANTY

| | |
|----------|-----------------------------------|
| Factory | 6-months limited warranty |
| Extended | Up to 30 months B.E.S.T. coverage |



©2016 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Maverick XC base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am



Can-AmOffroad.com