©OUTLANDER™ MAX XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- · Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels
- 26-in. ITP[†] Terracross radial tires
- Painted plastics for premium look
- Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ[™] system

- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- · Raised floorboards
- 5.7-gal (21.4 L) water-resistant rear compartment
- 625-W magneto



Black & Can-Am Red / 650 / 850 / 1000R Intense Red / 650 / 850 / 1000R

Mossy Oak[†] Break-Up Country Camo[†] / 650 / 850

ENGINES	650	850	1000R	
Туре	62 hp, Rotax 649.6 cc V-twin, liquid cooled	78 hp, Rotax 854 cc V-twin, liquid cooled	91 hp, Rotax 976 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fue	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking			
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential			
Power Steering	Tri Mada Dynamic Power Steering (DPS)			

Power Steering	Tri-Mode Dynamic Power Steering (DPS)				
SUSPENSIONS					
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel				
Front Shocks	0il				
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel				
Rear Shocks	0il				

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	\$
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CA	APACITIES
LxWxH	94 x 48 x 53 in. (238.8 x 121.9 x 135 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Engine / Dry Weight*	650: 827 lb (375 kg) 850: 874 (396 kg) 1000R: 900 lb (408 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES				
Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters,gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
			Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
			Seat	Convertible Rack System (CRS)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers handlebar wind deflectors, mudgua	,		

Λl				
		ā۱		

Factory 6-months limited warranty
Extended Up to 36 months B.E.S.T. coverage

©2018 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. "Base model dry weight shown. "Visco-Lok is a trademark of GKN Viscodrive GmbH. "All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP Ply recommends that all AV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the AIV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext 227, ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol /drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.



