

Dimensions

Imperial	SP-1225G
Empty Weight	190 lb
Overall Length	30" excl. trailer tongue
Overall Height	30"
Overall Width	44"

Metric	SP-1225G
Empty Weight	86.2 kg
Overall Length	76.2 cm excl. trailer tongue
Overall Height	76.2 cm
Overall Width	111.8 cm

Operational

Imperial	SP-1225G
Capacity (Volume)	12.0 cu ft
Capacity (Weight)	960 lb
Spreading Width	Up to 40' @ 5 mph

Metric	SP-1225G
Capacity (Volume)	0.3 cu m
Capacity (Weight)	435.5 kg
Spreading Width	12.2 m @ 8 km/h

Electrical

Imperial	SP-1225G
Speed Control	Controlled by tow vehicle ground speed

Metric	SP-1225G
Speed Control	Controlled by tow vehicle ground speed

Construction

Imperial	SP-1225G
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Spinner Drive Assembly	Ground-driven transmission
Spinner	12" adjustable stainless steel spinner
Mounting	Integral trailer

Metric	SP-1225G
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly
Spinner Drive Assembly	Ground-driven transmission
Spinner	30.5 cm adjustable stainless steel spinner
Mounting	Integral trailer

Standard Equipment

<i>Imperial</i>	<i>SP-1225G</i>
Cover	Standard

<i>Metric</i>	<i>SP-1225G</i>
Cover	Standard