

**Dimensions**

<b>Imperial</b>	<b>SP-2200</b>	<b>SP-2400</b>
Empty Weight	353 lb	326 lb
Overall Length	18"	14"
Overall Height	20"	24"
Overall Width	96"	84"
Hopper Length	17"	17"
Hopper Width	95½"	84"

<b>Metric</b>	<b>SP-2200</b>	<b>SP-2400</b>
Empty Weight	160.1 kg	147.9 kg
Overall Length	45.7 cm	35.6 cm
Overall Height	50.8 cm	60.9 cm
Overall Width	243.8 cm	213.4 cm
Hopper Length	43.2 cm	43.2 cm
Hopper Width	242.6 cm	213.4 cm

***Operational***

<b><i>Imperial</i></b>	<b><i>SP-2200</i></b>	<b><i>SP-2400</i></b>
Spreading Width	Up to 40'	Up to 40'

<b><i>Metric</i></b>	<b><i>SP-2200</i></b>	<b><i>SP-2400</i></b>
Spreading Width	Up to 12.2 m	Up to 12.2 m

## Electrical

<b>Imperial</b>	<b>SP-2200</b>	<b>SP-2400</b>
Speed Control	Digital, self-diagnosing dual variable-speed control with auto reverse	Digital, self-diagnosing dual variable-speed control with auto reverse
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

<b>Metric</b>	<b>SP-2200</b>	<b>SP-2400</b>
Speed Control	Digital, self-diagnosing dual variable-speed control with auto reverse	Digital, self-diagnosing dual variable-speed control with auto reverse
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

## Construction

<b>Imperial</b>	<b>SP-2200</b>	<b>SP-2400</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	Dual 12-volt DC motor mounted in weather resistant enclosure	Dual 12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Compact, independent weather-tight patented motor transmission	Compact, independent weather-tight patented motor transmission
Spinner	12" heavy-duty urethane spinner with integral hub assembly	12" heavy-duty urethane spinner with integral hub assembly
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Auger	5" heavy-duty variable pitch steel flighting	5" heavy-duty variable pitch steel flighting
Mounting	Universal mounting kit to fit most dump bodies (some fabrication required)	Universal mounting kit to fit most dump bodies (some fabrication required)

<b>Metric</b>	<b>SP-2200</b>	<b>SP-2400</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	Dual 12-volt DC motor mounted in weather resistant enclosure	Dual 12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Compact, independent weather-tight patented motor transmission	Compact, independent weather-tight patented motor transmission
Spinner	30.5 cm heavy-duty urethane spinner with integral hub assembly	30.5 cm heavy-duty urethane spinner with integral hub assembly
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Auger	12.7 cm heavy-duty variable pitch steel flighting	12.7 cm heavy-duty variable pitch steel flighting
Mounting	Universal mounting kit to fit most dump bodies (some fabrication required)	Universal mounting kit to fit most dump bodies (some fabrication required)

**Standard Equipment**

<b>Imperial</b>	<b>SP-2200</b>	<b>SP-2400</b>
Vibrator	Standard heavy-duty 12-volt DC	Standard heavy-duty 12-volt DC
Inverted "V"	Patented adjustable vibrating material flow facilitator	Patented adjustable vibrating material flow facilitator
Work Light	Yes	Yes

<b>Metric</b>	<b>SP-2200</b>	<b>SP-2400</b>
Vibrator	Standard heavy-duty 12-volt DC	Standard heavy-duty 12-volt DC
Inverted "V"	Patented adjustable vibrating material flow facilitator	Patented adjustable vibrating material flow facilitator
Work Light	Yes	Yes