

## Construction

<b>Imperial</b>	<b>32200</b>
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly with integral vertical rib construction
Motors	Dual, 12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Compact, independent weather-tight patented motor transmission
Spinner	12" powder coated steel with cupped fins
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Auger	3" transverse high-flow auger
Mounting	Positive locking mount with bolt-down kit and ratchet-strap assist

<b>Metric</b>	<b>32200</b>
Frame	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly with integral vertical rib construction
Motors	Dual, 12-volt DC motor mounted in weather resistant enclosure
Spinner Drive Assembly	Compact, independent weather-tight patented motor transmission
Spinner	30.5 cm powder coated steel with cupped fins
Auger Drive Assembly	Heavy-duty solid steel construction with maximum-torque motor transmission drive
Auger	7.6 cm transverse high-flow auger
Mounting	Positive locking mount with bolt-down kit and ratchet-strap assist

## Dimensions

<b>Imperial</b>	<b>32200</b>
Empty Weight	280 lb
Overall Length	64"
Overall Height	27"
Overall Width	48.5"
Floor Length	45"
Floor Width	34"
Hopper Length	53"
Hopper Width	48.5"

<b>Metric</b>	<b>32200</b>
Empty Weight	127 kg
Overall Length	162.6 cm
Overall Height	68.6 cm
Overall Width	123.2 cm
Floor Length	114.3 cm
Floor Width	86.4 cm
Hopper Length	134.6 cm
Hopper Width	123.2 cm

## Electrical

<b>Imperial</b>	<b>32200</b>
Speed Control	Digital, self-diagnosing dual variable-speed control
Wiring Harness	Completely loomed with molded plugs

<b>Metric</b>	<b>32200</b>
Speed Control	Digital, self-diagnosing dual variable-speed control
Wiring Harness	Completely loomed with molded plugs

## Operational

<b>Imperial</b>	<b>32200</b>
Capacity (Volume)	Struck 11.0 cu ft
Capacity (Weight)	880 lb
Spreading Width	Up to 30'

<b>Metric</b>	<b>32200</b>
Capacity (Volume)	Struck 0.31 cu m
Capacity (Weight)	399.2 kg
Spreading Width	9.1 m

## Standard Equipment

<b>Imperial</b>	<b>32200</b>
Top Screen	5/16" steel rod construction with grid pattern
Cover	Fitted tarp
Vibrator	Standard heavy-duty 12-volt DC
Inverted V	Patented vibrating inverted "V" to maximize material flow
Brake Light	No
Work Light	No

<b>Metric</b>	<b>32200</b>
Top Screen	0.8 cm steel rod construction with grid pattern
Cover	Fitted tarp
Vibrator	Standard heavy-duty 12-volt DC
Inverted V	Patented vibrating inverted "V" to maximize material flow
Brake Light	No
Work Light	No