



MODEL 135/150 FIXED GOOSENECK BEAVERTAIL



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features

Model 135 / 150 Fixed Gooseneck Beavertail

S=Standard O=Optional

MODEL 150	50 TON	100,000 lbs.	MODEL 150	50 TON	100,000 lbs.
MODEL 135	35 TON	70,000 lbs.	MODEL 135	35 TON	70,000 lbs.
MAIN FRAME			SUSPENSION		
- Fabricated 80,000 and 100,000 PSI	S	S	- Multi-Leaf Springs 45,000 lb. Capacity	S	S
- Four Beam Design	S	S	- Multi-Leaf Springs 67,200 lb. Capacity H9700/60" Spread	O	O
- Capacity - 70,000 lb. Distributed / 50,000 lb. Concentrated in 10'	S	S	- Neway Air Ride RLU228 22,500 lb. Capacity	O	O
- Capacity - 100,000 lb. Distributed / 70,000 lb. Concentrated in 10'	S	S			
KINGPIN SETTING			BRAKES		
- 18" Setting	S	S	- Automatic Slack Adjusters	S	S
- 84" Swing Clearance	S	S	- Full Air with Spring Brakes	S	S
			- ABS, Rockwell 4S2M	S	S
CROSSMEMBERS					
- 4" Jr. I-Beam on 8" Centers	S	S	OIL SEAL HUBS		
			- Internal Mated Assembly	S	S
DECK AND FEATURES			TIRES / WHEELS		
- 102" Width	S	S	- 235/75R 17.5 Double Coin	S	S
- Lower Deck Length	S	S	- Hub Pilot / Steel Outboard Brake Drum	S	S
135-27 3/4", 29 3/4", 32 3/4"	S	S			
150-29 3/4", 32 3/4"	S	S			
- 90° Slope Drop	S	S	RIMS		
- 37 1/2" Deck Height (Loaded)	S	S	- 17.5x6.75 Tubeless	S	S
- 1 1/8" Nominal, Apitong (Lower Deck)	S	S	- 17.5 Aluminum Wheels (8-Bolt Polished)	O	O
- 13" Loaded Ground Clearance	S	S			
UPPER DECK WINCH OPTIONS			TIRES & RIMS		
- 12,000 lb. Worm Gear	O	O	- Spare Double Coin Tire and Hub Pilot Type Rim (235/75R 17.5)	O	O
- 20,000 lb. Planetary	O	O	- 235/75R 17.5 Michelin Tires in Lieu of Standard	O	O
- 20,000 lb. Worm Gear Winch	O	O	- 255/70R 22.5 Michelin Tires in Lieu of Standard	O	O
- Cable Roller Guide for Winch - 12,000 lb. or 20,000 lb. Slope or Upper Deck	O	O	- Hubometer	O	O
			- 255/70R 22.5 Double Coin Tires in Lieu of Standard Double Coin	O	O
TIE DOWNS / CHAIN GOTCHAS					
- Double Key Hole Chain Slots Located on 24" Centers	S	S	HYDRAULIC POWER SOURCE		
- "D" Ring Bolt-On at Winch (each) (Two Locations Available)	O	O	- Air Shift PTO and Wet Kit for Tractor - Not Installed	O	O
- Flush Mounted "D" Rings (each)	O	O	- Installation of PTO and Wet Kit	O	O
			- Hydraulic Quick Couplers 1 Male / 1 Female (Matches Trailer)	O	O
TOOL BOX					
- Twin Lockable Upper Deck Mounted with Lockable Door 7" H x 34" W x 29" D	S	S	HYDRAULIC HOOK UP		
			- Hydraulic Quick Couplers 2,500 PSI - 15 GPM	O	O
DECK ACCESSORIES					
- Lower Deck Lockable Tool Box (Curb Side or Street Side)	O	O	AIR / ELECTRICAL CONNECTION		
(42" W x 28" D x 9" H)	O	O	- 7-Way Receptacle (Electrical)	S	S
- 96" Width Not Available	O	O			
SLOPE RAMP			LIGHTS		
- 5' Aluminum Ramps (Portable) 8,000 lb. Capacity Each	O	O	- Grote "SuperNova" LED 10-Year Warranty, Grote "Ultra Blue Seal" Wiring Harness	S	S
- Upper Deck Ramp (Air Operated)	O	O	7-Year Warranty	S	S
- Landoll Traction Ramps (Steel)	O	O	- Center Mounted Side Turn Signal	S	S
BULKHEADS					
- 16" / 24" 2-Position Bulkhead / Front Extension (Solid)	O	O	FINISH / COLOR		
- 48" High Mesh 102" or 96" Wide	O	O	- Steel Grit Shot Blast to Bright Metal	S	S
- Bolt-On Binder Storage Rack for 48" Bulkheads	O	O	- Epoxy Primer	S	S
- LED Work Light-Dual (Mounted on Bulkheads)	O	O	- Acrylic Urethane White, Black, Yellow, Blue, Red, Green	S	S
- Spare Tire Carrier 48" Bulkhead Front Mounted	O	O			
- Spare Tire Carrier 48" Bulkhead Rear Mounted	O	O	RAMPS		
- Dual Spare Tire Carrier 48" Bulkhead, Front Mounted	O	O	- 5' Self-Cleaning Adjustable Spring Assisted Flip-Over	S	S
			- Heavy Duty Crawler Ramp (Wood Filled)	O	O
PARKING STANDS			- Third Ramp-Self-Cleaning or Wood Filled	O	O
- Two Speed Landing Gear	S	S			
- Pin Drop (Lieu of Standard)	O	O	BEAVERTAIL		
			- 68" Self-Cleaning Beavertail	S	S
AXLES			- Apitong Wood Covered Beavertail	O	O
- (2) 25,000 Dual Tire, Oil Bath Bearings	S	S	- Traction Bars for Wood Covered Beavertail	O	O
- (3) 25,000 Dual Tire, Oil Bath Bearings	S	S			
			WEIGHT		
			- 135-40 12,000 lbs. +/- 3%	S	S
			- 150-48 14,500 lbs. +/- 3%	S	S

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!



135/150Fixed/0914