




# **MODEL 302/305/314 BOTTOM DUMP TRAILERS**



**Proven Solutions for Your Hauling Needs!**  
**1-800-428-5655 | [www.landoll.com/trailers](http://www.landoll.com/trailers)**



# Standard & Optional Equipment / Features

## Model 302 / 305 / 314 Bottom Dump Trailers



S=Standard O=Optional

MODEL 302	2 AXLE	21 CUBIC YARD
MODEL 305	3 AXLE	21 CUBIC YARD
MODEL 314	4 AXLE PUP	15 CUBIC YARD
<b>ACCESSORIES</b>		
- Push Bar with Underride Protection	O	O
- Hitch Kit for Tandem Hitches	O	O
- Shed Plates	O	O
- Side Board Brackets	O	O
- Window Deflector - Heavy Duty	O	O
<b>AXLES</b>		
- (2) 25,000 lb. Dual Tire, Oil Bath Bearings		S
- (3) 25,000 lb. Dual Tire, Oil Bath Bearings	S	
- (4) 25,000 lb. Dual Tire, Oil Bath Bearings	S	
<b>BRAKES</b>		
- 7x16.5 Full Air	S	S
- Automatic Slack Adjusters	S	S
- Brake Priority Valve	S	S
- Outboard Brake Drums	S	S
<b>CAPACITY</b>		
- 15 Cubic Yards	S	
- 21 Cubic Yards		S
<b>COLOR</b>		
- White, Black, Yellow, Blue, Red, Green	S	S
- Steel Grit Shot Blast to Bright Metal, Epoxy Primer	S	S
<b>CONVERTER DOLLY</b>		
- 2 Axle - 40,000 lb. Capacity		O
<b>DIMENSIONS</b>		
- Height - 8'11"	S	
- Height - 8'9"		S
- Overall Length - 26'2"	S	
- Overall Length 35' or 39'1"		S
- Overall Width - 8'	S	S
- Target Area - 16'L x 88"W		S
- Target Area - 12'4"L x 88"W	S	
<b>FENDERS</b>		
- Front Full	O	O
- Rear Weld-On with Mudflaps	S	S
<b>LIGHTS</b>		
- Grote "SuperNova" LED 10-Year Warranty, Grote "Ultra Blue Seal" Wiring Harness 7-Year Warranty	S	S
- Center Mounted Side Turn Signal	S	S

MODEL 302	2 AXLE	21 CUBIC YARD
MODEL 305	3 AXLE	21 CUBIC YARD
MODEL 314	4 AXLE PUP	15 CUBIC YARD
<b>GATE</b>		
- Single - Air Operated - Window Type	S	S
- Air Cylinders 7" x 30"	S	S
- Air Cylinder Lubricators - Water Separator	S	S
- Air Tank - 40 Gallon	S	
- Air Tank - 60 Gallon		S
- Controls		
- Jogging for Asphalt Windowing	O	O
- Manual Valve	S	S
- Truck Switches	O	O
- Openings		
- 58" x 117"		S
- 59" x 75"	S	
<b>HITCH</b>		
- Fifth-Wheel King Pin with Lateral Rocking Plate		S
<b>SUSPENSION</b>		
- (6) Spring 3 Leaf		S
- (4) Spring 3 Leaf		S
- (4) Spring 3 Leaf Front & Rear	S	
- Air Ride Suspension		O
<b>TIRES</b>		
- 11.00 22.5 LRF Tubeless Bias	S	S
- 11.00 24.5 LRF Tubeless Bias	O	O
- 11R22.5	O	O
- 11R24.5	O	O
<b>WHEELS / HUBS</b>		
- Steel Hub Pilot / Outboard Drums	S	S
- Aluminum Hub / Centrifuse Outboard Drums	O	O
- 22.5x8.25 Tubeless 10-Hole Aluminum or Steel Hub Pilot	O	O
- 24.5x8.25 Tubeless 10-Hole Aluminum or Steel Hub Pilot	O	O
<b>WEIGHT (ESTIMATED)</b>		
- 35' - 10,750 lb. or 39'1" - 11,050 lb.		S
- 35' - 12,600 lb. or 39'1" - 12,945 lb.	S	
- 26'2" - 13,115 lb.	S	

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.

**Call 1-800-428-5655**

**Proven Solutions for Your Hauling Needs!**



**[www.landoll.com/trailers](http://www.landoll.com/trailers)**

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

**Remember: Quality is Always a Bargain!**



**Intertek**  
302-305-314  
061715