



MODEL 326/327/329 DETACHABLE GOOSENECK



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features

Model 326/327/329 Detachable Gooseneck

S=Standard O=Optional

MODEL 326	35 TON	70,000 lbs.
MODEL 327	50 TON	100,000 lbs.
MODEL 329	60 TON	120,000 lbs.
MAIN FRAME		
- Fabricated 16", 100,000 PSI Flange	S	S S
- Capacity - 70,000 lb. in 16'		S
- Capacity - 100,000 lb. in 16'		S
- Capacity - 120,000 lb. in 10'	S	
KINGPIN SETTING		
- 84" Swing Clearance		S S
- 113" Swing Clearance (13' Neck)	S	O
CROSSMEMBERS		
- 8" High Tensile I-Beams on 24" Centers		S S
- 8" High Tensile I-Beams on 20" Centers	S	
GOOSENECK, DECK & ACCESSORIES		
- 10'7"		S S
- 13" Gooseneck with 86" and 113" Swing Clearance		O
- 13' HD with Provision for Flip Ext.	S	
- 102" Wide	S	S S S
- 8" Loaded Ground Clearance	S	S S S
- 24" Loaded Deck Height	S	S S S
- Fifth-Wheel Type Automatic Gooseneck Lock with Lock / Unlock Visual from Tractor	S	S S S
- Centralized Grease System	S	S S S
- Automatic Slack Adjusters	S	S S S
- Rail Stiffeners	S	S S S
- Ramp Brackets and Outtrigger Brackets	S	S S S
- Boom Trough	S	S S S
- Front Bolsters	S	S S S
TIE DOWNS / CHAIN GOTCHAS		
- 8 "D"-Rings		S
- 10 "D"-Rings	S	S
STORAGE AREA		
- 41"W x 24"L x 10"D Between Main Frames	S	S
- 41"W x 20"L x 10"D Between Main Frames		S

MODEL 326	35 TON	70,000 lbs.
MODEL 327	50 TON	100,000 lbs.
MODEL 329	60 TON	120,000 lbs.
SUSPENSION / AXLES		
- Newway Air Ride (RLU250) 25,000 lb. Capacity	S	S S
- (2) 25,000 lb. Dual Tire, Oil Bath Bearings		S
- (3) 25,000 lb. Dual Tire, Oil Bath Bearings	S	S
BRAKES		
- 16.5x7 Full Air / Spring Brakes (Two Axles) ABS, 4S2M / Center Axle Indirect	S	S S
TIRES / RIMS		
- 255/70R 22.5 LRH Radial		S S
- 295/75R 22.5 LRG Radial	S	
- 22.5x8.25 10-Bolt Hub Pilot	S	S S
HYDRAULIC HOOK UP		
- Hydraulic Quick Couplers / 2,500 PSI - 15 GPM	S	S S
LIGHTS		
- Grote "SuperNova" LED 10-Year Warranty	S	S S
- Grote "Ultra-Blue Seal" Wiring Harness 7-Year Warranty	S	S S
FINISH / COLOR		
- Steel Grit Shot Blast to Bright Metal	S	S S
- Zinc Rich Primer	S	S S
- TGIC Polyester Power Coat	S	S S
White, Black, Yellow, Blue, Red, Green		
WEIGHT (ESTIMATED)		
- 13,250 lbs. (44') +/- 3%		
- 18,900 lbs. (48') +/- 3%		S
- 22,500 lbs. (51') +/- 3%	S	
MORE OPTIONS AVAILABLE -- CONSULT FACTORY		

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!



326-327-329/0914