



# **MODEL 334/336 CAR CARRIER TRAILER**



Cordless Hydraulic Controls



Rugged Guide Rails on  
Lower and Upper Decks



Manual Hydraulic Controls



One Winch per Vehicle  
Upper and Lower Deck



Adequate Clearance on  
Wide Variety of Vehicles



Tilt Cylinder - Major Steel  
Components Powder Coated



***Proven Solutions for Your Hauling Needs!***  
**1-800-428-5655 | [www.landoll.com/trailers](http://www.landoll.com/trailers)**



# Standard & Optional Equipment / Features

## Model 334 (4 Car) / 336 (6 Car) Carrier Trailer

S=Standard O=Optional

MODEL 334		
MODEL 336		
<b>MAIN FRAME</b>		
- Full Aluminum Extrusion Heat Treated	S	S
<b>CROSSMEMBERS</b>		
- 9" Aluminum Floor Plate with Extruded Integral Crossmembers on 3" Centers	S	S
<b>PARKING STANDS</b>		
- Pin Drop	S	S
<b>AXLES</b>		
- (1) 25,000 lb. Dual Tire, Oil Bath Bearings	S	S
- (2) 25,000 lb. Dual Tire, Oil Bath Bearings	S	S
<b>SUSPENSION</b>		
- Neway RLU228 Air Ride 22,500 lb. Capacity	S	S
<b>BRAKES</b>		
- 12.25x7.5 Full Air Spring Brake ABS, 2S1M	S	S
- 12.25x7.5 Full Air Spring Brake ABS, 4S2M	S	S
<b>PIN SETTING</b>		
- 34"	S	S
- 15"	S	S
<b>SWING CLEARANCE</b>		
- 55"	S	S
- 75"	S	S
<b>WIDTH</b>		
- 102"	S	S
<b>LENGTH</b>		
- 35'	S	S
- 48'	S	S
<b>TIE DOWNS</b>		
- 8 "D" Rings - 6 Key Holes on Each Approach	S	S
<b>COLOR</b>		
- Metal Parts Powder Coated Black	S	S
<b>HYDRAULIC WINCH</b>		
- 4-Worm Gear 8,000 lb. with 65' 3/8" Cable	S	S
- 6-Worm Gear 8,000 lb. with 65' 3/8" Cable	S	S
- Winch Deduct - Per Winch - Maximum of Two May Be Deducted	O	O
<b>TOP DECK ADJUSTMENT CYLINDER</b>		
- 4 Rephase for Level Lift	S	S
- 6 Rephase for Level Lift	S	S

MODEL 334		
MODEL 336		
<b>LOAD ANGLE</b>		
- Minimum 8° Lower Deck	S	S
- Minimum 17° Upper Deck	S	S
- Maximum 18° Lower Deck	S	S
- Maximum 28° Upper Deck	S	S
<b>UPPER DECK</b>		
- Hydraulic Adjustable 24" Vertical Travel with Safety Lock on 2" Increments	S	S
<b>HYDRAULIC CONTROLS</b>		
- Wireless Remote on Manual Controls on all Functions with Hand Held Control Box and Shoulder Strap	S	S
<b>OVER THE CAB INSTALLATION</b>		
- One Car Over Cab can be Installed on a Variety of Trucks (Contact Factory).	O	O
- Installation of Safety Buzzer-In Cab for One Car Over Cab	O	O
<b>ACCESSORIES</b>		
- Left Hand Tool Box	S	S
- In-Cab Holder Control Box with Safety Buzzer	S	S
- Automatic Slack Adjusters	S	S
- Bridle Adapter Plate (each)	O	O
- Combination Chain (each)	O	O

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



Maximum Clearance 81"

**Call 1-800-428-5655**

**Proven Solutions for Your Hauling Needs!**

**[www.landoll.com/trailers](http://www.landoll.com/trailers)**

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

**Remember: Quality is Always a Bargain!**

