



MODEL 825/835 AG DETACHABLE GOOSENECK



- Easily Adjustable Ground Clearance from 7" to 17" / 22"
- Transport at any Height while Neck Remains Locked



- RUST FREE Aluminum Pullouts to 13' Width (7000 lb. capacity each)
- Pullouts are Strong as Steel yet Save 1000 lb. of Weight
- Pullouts Adjustable on 6" Increments
- Heavy-Duty Steel Front Pullout Easily Adjusted by the Drivers



- Low Profile Front Approach
- Four Wheel or Tricycle Units can be Easily Loaded
- No Heavy Ramps
- Safe Loading Directly on Lower Deck
- Increased Driver Confidence while Loading



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features

Model 825 / 835 Ag Detachable Gooseneck Trailer

S=Standard O=Optional

MODEL 835 AG	35 TON	70,000 lbs.	MODEL 825	27.5 TON	55,000 lbs.
MAIN FRAME			WINCHES AND ACCESSORIES		
- Fabricated 100,000 PSI Four Beam Frame	S		- Worm Gear 12,000 lb. with 85' of 1/2" Cable	O	O
- Capacity - 55,000 lb. Distributed / 50,000 lb. Concentrated in 16'	S		- Worm Gear 20,000 lb. with 85' of 5/8" Cable	O	O
- Capacity - 70,000 lb. Distributed / 60,000 lb. Concentrated in 12'	S		- Planetary 30,000 lb. with 85' of 5/8" Cable	O	O
KINGPIN SETTING	S		LIFT CYLINDER		
- 15" Pin Setting - 84" Swing Clearance 12' G/N	S		- (2) 6" x 30" Horizontal Mount 70,000 lb. Capacity	S	S
- 15" Pin Setting - 72" Swing Clearance 10'7"	O		AXLES		
CROSSMEMBERS	O		- (2) 25,000 lb. Dual Tire, Oil Bath Bearings	S	S
- 5" x 3" High Tensile Strength Tubing on 18" Centers	S		SUSPENSION		
GOOSENECK, DECK AND ACCESSORIES	S		- Neway Air Ride, 25,000 lb. Capacity	S	S
- 12' Gooseneck	S		- Centralized Grease System	S	S
- 10'7" Gooseneck	S		- Air Raise and Lower Valve	O	O
- 102" Removable Aluminum Front and Rear Decks	O		- Digital Air Weigh Scale System	O	O
- 102" Width	O		BRAKES / HUBS		
- 120" Width (Some 835 Models)	O		- Automatic Slack Adjusters	S	S
- Lower Deck Length 27'10" through 29'10", with 49' or 51' Overall Length	S		- 16.5 x 7 Full Air / Spring Brakes (ABS, 4S2M)	S	S
- Lower Deck Length 26'8" through 31'8", with 48' or 53' Overall Length	S		- 22.5 x 8.25 Hub Pilot / Steel Outboard Hubs	S	S
- 17" Deck Height (Loaded)	S		TIRES		
- 18 1/4" Deck Height (Loaded)	S		- 255/70R 22.5 LRH	S	S
- 1 1/2" Nominal, Apitong Full Width	S		- Spare Tire and Hub Pilot Type Rim (255/70R 22.5)	O	O
- 27" Aluminum Telescoping Side Extensions	S		WHEEL ACCESSORIES		
- Flag and Banner Package (6 Flags & 2 Overwidth Banners)	O		- Aluminum Wheel 7.5x22.5	O	O
TIE DOWNS / CHAIN GOTCHAS	S		- Hubometer	O	O
- Double Key Hole Chain Slots Located on 36" Centers	S		HYDRAULIC POWER SOURCE		
- (2) D-Rings at Base of Rear Trunnion Flush Mounted on Top of Inner Beams	S		- Air Shift PTO and Wet Kit for Tractor - Not Installed	O	O
- (4) D-Rings - Gooseneck Beam (Bolt On)	O		- 11 HP Honda Engine Package with Front Cover Front Extension Mount	O	O
- (4) D-Rings - Trunnion Main Beam (Bolt On)	O		- 25 HP Kohler Engine Package	O	O
- Side Mounted Nylon Strap / Chain Tie Downs	S		LIGHTS		
- Side Mounted D-Rings on 36" Centers	S		- Grote "SuperNova" LED 10-Year Warranty	S	S
- (2) D-Rings Web-Mounted Top of Trunnion	S		- Grote "Ultra-Blue Seal" Wiring Harness 7-Year Warranty		
- (2) D-Rings Rear of Trunnion, Flush Mounted on Top of Inner Beams	S		FINISH / COLOR		
- (2) D-Rings Back of Gooseneck	S		- Steel Grit Shot Blast to Bright Metal	S	S
- (2) D-Rings at Top of Trunnion Slope (Outer Web)	S		- TGIC Polyester Powder Coat	S	S
TOOL BOX	S		White, Black, Yellow, Blue, Red, Green		
- 11"H x 47"W x 25"D ("C" Series 12' G/N)	S		WEIGHT (BASE)		
- 11"H x 33"W x 25"D Street Side ("C" Series 10'7" G/N)	S		- 49' - 825 - 18,000 lb. +/- 3%	S	
- 24"H x 14"W x 22.5"D Curb Side ("D" Series)	O		- 51' - 825 - 18,300 lb. +/- 3%	S	
			- 48', 51' - 835AG - 18,400 lb., 18,900 lb. +/- 3%	S	
			- R-53' - 835AG - 20,700 lb. +/- 3%	S	
			- S120-53' - 835AG - 18,300 lb. +/- 3%	S	
			- S60-53' - 835AG - 19,300 lb. +/- 3%	S	
			ESTIMATED WEIGHTS		



Manufactured by Landoll Corporation, the centralized lube system provides remote grease zerks to each individual greaseable point on the trailer undercarriage including the slack adjusters and camshaft bearings, which both require regular grease for optimum performance. Maintenance time and costs are reduced significantly.

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!

