




MODEL LT1016 UTILITY TAG TRAILER



A 6"channel iron frame under the main frame for superior strength. A solid formed 6" height headboard for protection.
(Stake pockets shown for optional removable sideboards)



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features

Model LT1016 Utility Tag Trailer



S=Standard O=Optional

MODEL LT1016 TILT DECK	
DIMENSIONS	S S S S
- 16' Flat Deck	S
- 22" Loaded Deck Height	S
- 80" Wide Between Fenders	S
- 102" O/A Width	S
CAPACITY	S S S S
- 10,000 lbs.	S
- 3,150 lb. Trailer Weight	S
- 13,150 lb. GVWR	S
MAIN FRAME	S S S S
- 6" Channel	S
- 4" Jr. I-Beam, 80,000 PSI Yield on 24" Centers	S
- 6" Channel Hitch Frame	S
- Tool Box Under Deck	S
AXLES	S
- (2) 6,000 lb. Torflex, E-Z Lube	S
TIRES AND BRAKES	S S
- LT235/80R16 LRE	S
- Both 12"x2" Electric Brakes	S
DECK	S S S O
- 2" Nominal CA-B Cooper Azole Treated Pine	S
- (4) 5/8" D-Rings	S
- Stake Pockets 2 per Side	S
- Sideboards	O
TIILT DECK	S S S
- 2 1/2" x16" Cushion Cylinder	S
- Approach Plate Landoll Traction Plate	S
- Load Angle - 12.5°	S
ACCESSORIES	S S S O O
- Fenders - HD 14 Gauge with Back	S
- Running Boards with Anti-Skid Tape	S
- White, Black or Yellow Powder Coat Paint	S
- 8,000 lb. Ramsey Electric Winch	S
- Spare Tire Carrier	O
PHOTOS MAY SHOW OPTIONAL EQUIPMENT	

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.

