



# LOADOLL II



#### **Dual Hydraulic Controls**

Well protected, illuminated hydraulic controls are located just rear of the axle.



**Proven Solutions for Your Hauling Needs!**  
**1-800-428-5655 | [www.landoll.com/trailers](http://www.landoll.com/trailers)**



# Standard & Optional Equipment / Features

## Loadoll II

S=Standard O=Optional



MODEL LOADOLL II		MODEL LOADOLL II	
<b>MAIN FRAME</b>	<b>S</b>	<b>HITCH</b>	<b>S</b>
- 10,000 lb. Distributed Over Full Length of Deck	<b>S</b>	- None	<b>O</b>
- Rigid Tubular Steel Sub-Frame (Powder Coated Black), Full Length High Quality Polymer Wear Pad (Deck Mounted)	<b>S</b>	- Independent Wheel Lift, Rear Tilt	<b>O</b>
- Positive Bed Hold-Down-Frame Mounted with Safety Anti-Lock Tilt Lockout	<b>S</b>	- Independent Wheel Lift, Front and Rear Tilt	<b>O</b>
<b>CROSSMEMBERS</b>	<b>S</b>	- Independent Stabilizer Leg, Rear Tilt	<b>O</b>
- 2" x 2" Square Tubing 11 Gauge 8" Centers	<b>S</b>	<b>TIE DOWNS</b>	<b>S</b>
<b>HYDRAULICS</b>	<b>S</b>	- Keyholes; (4) Front; (4) Midship; (4) Rear	<b>S</b>
- PTO Pump, Oil Reservoir	<b>S</b>	- (2) Front Mounted 6' Safety T-Hook and Grab Hook, V-Chain Bridle	<b>S</b>
- Direct Mounted Pump with Cable Shift PTO and Warning Light	<b>S</b>	<b>STORAGE AREA / TOOL BOX</b>	<b>S</b>
- Special Hot Shift PTO / Pump for Auto Transmission	<b>S</b>	- Chain and Binder Trays at Front of Deck with Sprayed on Rubberized Protection	<b>S</b>
<b>DECK AND FEATURES</b>	<b>S</b>	- (2) Chain Storage Trays at Wheel Lift, with (2) 6' Safety Chains with Grab Hook, T-Hook and J-Hook	<b>S</b>
- Adjustable Stabilizer Legs	<b>S</b>	- 30" Steel Tool Box 18" x 18" with Stainless Door	<b>O</b>
- Dual Hydraulic Control Work Stations	<b>S</b>	- 48" Steel Tool Box 18" x 18" with Stainless Door	<b>O</b>
- Toe Board 3/8" x 2-1/2" Tall Skid Plate 3/8" x 8 Wide	<b>S</b>	- 30" Steel Box 18" x 18" with Steel Door	<b>O</b>
- Ratchet Winches for 4" Nylon Strap	<b>S</b>	- 48" Steel Box 18" x 18" with Steel Door	<b>O</b>
- 3/16" Smooth Steel Deck	<b>S</b>	<b>ACCESSORIES</b>	<b>S</b>
- 3/16" Tread Plate	<b>S</b>	- Steel Bulkhead, Bed Mounted	<b>O</b>
<b>LIGHTS</b>	<b>S</b>	- Steel Bulkhead, Frame Mounted	<b>O</b>
- FMVSS Light Group with E-Chain Protection System, Dual Lighted Control Stations, Receptacle for Auxiliary Tow Lights, Backup Alarm	<b>S</b>	- Aluminum Bolt-On Bulkhead, Bed Mounted	<b>O</b>
<b>WINCH</b>	<b>S</b>	- Rear Work Lights Bulkhead Mounted	<b>O</b>
- 9,000 lb. Worm Gear with Manual Kickout and Spring Tension Plate, 3/8" x 50' Cable	<b>S</b>	- Rear Work Lights Bumper Mounted	<b>O</b>
		- Magnetic Tow Lights with 30' Coiled Cable	<b>O</b>
		<b>FINISH / COLOR</b>	<b>S</b>
		- Deck and Sub-Frame Powder Coat Black	<b>S</b>

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



### 9,000 lb. Winch Standard

The winch may be equipped with optional remote control. The bulkhead is bed mounted with two chain trays.



### Hydraulic System

The Loadoll II uses welded hydraulic cylinders with chrome plated rods for long trouble-free service.

**Call 1-800-428-5655**

**Proven Solutions for Your Hauling Needs!**

**www.landoll.com/trailers**



1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

**Remember: Quality is Always a Bargain!**

