



LOADOLL III



Hydraulic Control Box

A well-protected, illuminated hydraulic control box is located just rear of the axle.



Hydraulic System

The Loadoll III uses welded hydraulic cylinders with chrome plated rods for long trouble-free service.



Standard Stabilizer Bar

The heavy-duty stabilizer bar also serves as a dock level hydraulic lift that raises the bed to a maximum of 59" with 30,000 lb. capacity.



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers



Standard & Optional Equipment / Features

Loadoll III

S=Standard O=Optional

MODEL LOADOLL III		MODEL LOADOLL III	
MAIN FRAME		HITCH	
- Capacity - 30,000 lb. Distributed Over Full Length of Deck	S	- Hydraulic Independent Stabilizer Leg	S
CROSSMEMBERS		- Ag Style Hitch with 4-Prong Electrical Outlet (Double Clevis) or Ball Hitch (Ball Not Included)	O
- 3" Jr. I-Beam on 12" Centers	S	- Pintle Hook Eye, 6,000 lb. with 4-Prong Electrical Outlet	O
HYDRAULICS		- 5,000 lb. Independent Towbar with 4-Prong Electrical Outlet	O
- PTO Pump, Oil Reservoir	S	- 5,000 lb. Independent Wheel Lift with 4-Prong Electrical Outlet	O
- Live Hydraulic Quick Couplers at Rear	O		
- Dual Hydraulic Controls	O		
- Air Shift PTO in Lieu of Standard	O		
DECK / ACCESSORIES		BRAKE	
- 1 1/8" Apitong Wood	S	- Air Brake Glad Hands at Rear	O
- Full Height Frame Mounted Steel Cab Protector	S		
- 1/8" Steel Tread Plate over Pine Decking on 22', 24', 26' or 28' Bed	O		
- 6" Crossmember Spacing in Lieu of Standard on 22', 24', 26' or 28' Bed	O		
- Two-Step Ladder at Front Deck	O		
- Removable Side Rails	O		
LIGHTING / ELECTRICAL		TIE DOWNS	
- FMVSS Light Group with Midship Mounted Turn Signal	S	- Stake Pockets and Double Keyhole (Gotchas) Tie Down on 12" Centers	S
- (2) Halogen Work Light Bulkhead Mounted	O	- Recessed Tie Down "D" Rings (Not Available on 6" Crossmembers)	O
- (2) Halogen Work Lights, Wheel Lift	O	- Ratchet Winch for 4" Nylon Straps	O
- 4, 6 or 7-Way Electrical Outlet at Rear	O		
WINCH		TOOL BOX / STORAGE	
- 12,000 lb. Hydraulic Worm Gear with 60' 1/2" Cable	S	- (1) Tool Box Curbside with Paddle Latch & Lock 23" W x 15" H x 23" D	S
- 20,000 lb. Hydraulic Worm Gear with 60' 1/2" Cable	O	- Recessed Chain Storage Area at Front of Deck	O
- Remote Control for Winch (Street Side)	O	- Left Side Tool Box	O
- Wireless Remote Control Full Function	O		
- Cable Roller Guide 12,000 lb. or 20,000 lb. Winch	O		
- Halogen Work Light at Winch	O		
- Tie Down "D" Ring at Winch (Bolt-On)	O		

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.



Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!



Landoll-III/0914