



# POWER DITCHER



**3** YEAR  
WARRANTY

## Model D4P16A

- 540 RPM PTO and rotor speed
- Cutter head adjustable from 16" to 18", with 4 heat treated replaceable blades
- Adjustable cutting depth by regulating depth control skid and 3-point hitch
- Chain case 3" x 8", uses single 80 H roller chain w/ 15 hardened tooth sprockets
- Hitch, Cat. I or II 3-point or Cat. II quick hitch
- (2) Shear bolts, 5/16" grade 8
- (2) Parking stands
- Recommended PTO HP: 35-60
- Sapphire Blue Powder Coat Paint Standard

## Model D5P18A, D10P18A, and D10PH18A

- 540 RPM D5P18A, and 1,000 RPM on D10P18A and D10PH18A
- Cutter head adjustable from 18" to 20", with 4 heat treated replaceable blades – 740 RPM rotor speed
- Adjustable cutting depth by regulating depth control skid and 3-point hitch
- Chain case, 6" x 10" with bolt on top and bottom caps, uses double 80 chain and case hardened 16 tooth top sprocket and 22 tooth bottom sprocket for DP10 models. Sprockets are reversed on D5P18A
- Cat. II or III, 3-point or quick hitch
- (2) Shear bolts, 3/8" grade 8
- (2) Parking stands
- Recommended PTO HP: 50-100 with 540 PTO for D5P18A
- Sapphire Blue Powder Coat Paint Standard

Recommended PTO HP: 80-150 with 1,000 PTO for D10P18A and D10PH18A



## MODEL SPECIFICATIONS

Model Number	PTO RPM	Coupler Size	Estimated Weight
D4P16A	540	1-3/8"	355
D5P18A	540	1-3/8"	525
D10P18A	1,000	1-3/8"	525
D10PH18A	1,000	1-3/4"	530



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • [www.landoll.com](http://www.landoll.com)

Landoll continuously improves products. We reserve the right to make any changes in illustrations, specifications, equipment, and prices without prior notice and without changes on previous models.

