

NEW

SM240H

Ideal Acreage	15-45
Engine HP	36.9
Loader Lift Capacity	2,116 LBS.
Transmission	Hydrostatic
Optional cruise control	



Offering Yanmar craftsmanship and comfort in a compact, agile body, the SM240H provides powerful multi-functional capability with the ease of a clutch-less hydrostatic transmission. Getting your work done has never been so smooth.



ADVANCED TECHNOLOGY AND DESIGN

This extraordinary machine offers cutting-edge features, all expertly crafted for effortless use. From the convenient, foldable ROPS to the joystick-operated front-end loader, every aspect has been designed to enhance your land-working experience.

TRANSFORMATIONAL PERFORMANCE

With a Yanmar engine providing maximum torque at lower RPMs, it tackles heavy loads and implements. Enjoy one of the highest lift capacities on the market.

EXCEPTIONAL QUALITY

Providing extraordinary durability and reliability plus an ergonomic operator station, it exceeds industry standards in every way. It's a legacy your family will cherish for generations.



SM240H

COMPACT
UTILITY
TRACTOR




OPERATOR'S STEP OFFERS EASE CLIMBING ON AND OFF THE TRACTOR.



YANMAR BACKHOE WITH 16" BUCKET AVAILABLE AS A FACTORY OPTION.



DUAL BRAKES OFFER A TIGHT TURNING RADIUS.



OPERATOR'S CONTROLS ALL WITHIN REACH.

SPECIFICATIONS

Ideal Acreage	15-45
Engine HP	36.9
Loader Lift Capacity	2,116 LBS.
Transmission	Hydrostatic

WARRANTY COVERAGE

Tractor*	24 months or 2,000 hours (whichever comes first)
Powertrain*	10 years or 3,000 hours (whichever comes first)

*for non-commercial, home and residential use only

POWERTRAIN

Engine Manufacturer	Yanmar
Engine Gross Power	36.9 HP (27.5 kW)
PTO Power	27.5 HP (21.0 kW)
Rated Engine Speed	3,000 RPM
Clutch	-

CAPACITIES

Fuel Tank	9.0 gal. (34 L)
-----------	-----------------

DRIVETRAIN

Transmission Type	Hydrostatic
Rear Differential Lock	Foot Pedal Engagement
2WD/4WD Engagement	Selectable
PTO Type	Independent
PTO Control	Electric/Hydraulic
Rear PTO Speed	540 RPM

HYDRAULICS

Pump Capacity (Steering) @ Rated RPM	4.4 GPM (16.66 L/min)
Pump Capacity (Implement) @ Rated RPM	6.1 GPM (23.09 L/min)
Pump Capacity (Total) @ Rated RPM	10.5 GPM (39.75 L/min)
3-Point Hitch Category	1
3-Point Lift Capacity (Std.)	2,639 lbf. (1,197 kgf)
3-Point Lift Capacity at 24" (61 cm)	1,558 lbf. (707 kgf)
Remote Valves	Optional (1 or 2)
3rd Function Valve	Optional

DIMENSIONS AND WEIGHT

Minimum Ground Clearance	12.8" (325 mm)
Total Weight	3,020 lb. (1,370 kg)

FRONT END LOADER

RL505

Maximum Lift Height to Pivot Pin	101.5" (2,578 mm)
Lift Capacity to Maximum Height at Pivot Pin	2,116 lb. (960 kgf)
Breakout Force at Ground Level Pivot Pins	3,435 lb. (1,558 kgf)



To learn more or
find a dealer nearest
you, please visit
YanmarTractor.com

YANMAR has a corporate policy of continuous product improvement and development; therefore data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating a machine, read, understand, and follow all instructions of the manual and on the machine. YANMAR disclaims all representations, express or implied, or any liability from the use of this publication.