

NEW

SM475

Ideal Acreage	35-75
Engine HP	74
Transmission	Power Shuttle
Luxury cab with AC/heat and more	



Harnessing the highest HP Yanmar offers, the SM475 gives you the confidence to power through any job. Its purposeful design is intuitive to your needs so you can concentrate on the land.



ADVANCED TECHNOLOGY AND DESIGN

Equipped with a clutch-less power shuttle transmission for effortless operation. Adjust the power steering and tilt, all implements, and an integrated joystick-controlled mechanical self-leveling loader—all without leaving your seat.

TRANSFORMATIONAL PERFORMANCE

Specializing in precision tasks like trenching, it ensures greater impact with fewer passes. And its high-capacity fuel tank means it can tackle medium- to heavy-duty tasks for extended durations.

EXPERIENCE LUXURY

Boasting a dual-entry deluxe cab, advanced climate control, ergonomic operator station with digital command hub, and an immersive audio system, it empowers you to work your land in the utmost comfort.



SM475

UTILITY
TRACTOR



LUXURY CAB WITH ALL THE COMFORT AND CONTROLS AT YOUR FINGERTIPS.



FOOT THROTTLE OFFERS EASE OF WORK.



MECHANICAL SUSPENSION SEAT OFFERS MAXIMUM COMFORT.

SPECIFICATIONS

Ideal Acreage	35-75
Engine HP	74
Transmission	Power Shuttle
Luxury cab with AC/heat and more	

WARRANTY COVERAGE

Tractor*	24 months or 2,000 hours (whichever comes first)
Powertrain*	10 years or 3,000 hours (whichever comes first)

*for non-commercial, home and residential use only

POWERTRAIN

Engine Manufacturer	Deutz
Engine Gross Power	74 HP (55.4 kW)
PTO Power	64.1 HP (47.8 kW)
Rated Engine Speed	2,200 RPM
Clutch	Wet Multi Plate

CAPACITIES

Fuel Tank	23.8 gal. (90 L)
-----------	------------------

DRIVETRAIN

Transmission Type	Power Shuttle
Rear Differential Lock	Foot Pedal Engagement
2WD/4WD Engagement	Selectable
PTO Type	Independent
PTO Control	Electric/Hydraulic
Rear PTO Speed	540 RPM

HYDRAULICS

Pump Capacity (Steering) @ Rated RPM	5.8 GPM (22 L/min)
Pump Capacity (Implement) @ Rated RPM	10.3 GPM (39.1 L/min)
Pump Capacity (Total) @ Rated RPM	16.1 GPM (61.1 L/min)
3-Point Hitch Category	Category 2
3-Point Lift Capacity (Std.)	5,115 lbf. (2,320 kgf)
3-Point Lift Capacity at 24" (61 cm)	3,418 lbf. (1,550 kgf)
Remote Valves	Standard (2)
3rd Function Valve	Optional

DIMENSIONS AND WEIGHT

Minimum Ground Clearance	18.3" (465 mm)
Total Weight	6,052 lb. (2,745 kg)

FRONT END LOADER

RL505

Maximum Lift Height to Pivot Pin	133.8" (3,398 mm)
Lift Capacity to Maximum Height at Pivot Pin	3,325 lb. (1,508 kgf)
Breakout Force at Ground Level Pivot Pins	5,485 lb. (2,488 kgf)



To learn more or
find a dealer nearest
you, please visit
YanmarTractor.com

YANMAR has a corporate policy of continuous product improvement and development; therefore data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating a machine, read, understand, and follow all instructions of the manual and on the machine. YANMAR disclaims all representations, express or implied, or any liability from the use of this publication.