

TRACTORS / YM342



FEATURES

PERFORMANCE LINK TECHNOLOGY

SYNCHRONIZED SHUTTLE SHIFT TRANSMISSION

3-POINT HITCH FOR CATEGORY 1 AND 2 ATTACHMENTS

540E PT0

LOWER FUEL TANK POSITIONING

TELESCOPIC HITCH ARMS

ISOLATED MOUNT FLOORBOARD



CONVENIENCE AND COMFORT



PUT MORE POWER ON THE GROUND

 Synchronized shuttle shift allows you to quickly change between forward and reverse allowing effortless loader work.

★★★★★ PROVEN QUALITY

LIMITED POWERTRAIN

- Suitable for grading, material handling, and moving bales of hay.
- Gear drive transmission combined with Yanmar diesel engine gives you high torque and more usable PTO horsepower.



EFFICIENCY AND COMFORT BUILT RIGHT IN

- 540E PTO provides optimum operation at lower engine RPM resulting in less fuel consumption.
- All YM3 models include suspension seat, cup holder and isolated mount floorboard for reduced vibration to provide all-day comfort.
- Ideal for mowing and baling.



VERSATILITY WITH ATTACHMENTS

- Compatible with both category 1 and category 2 attachments.
- Telescopic hitch arm provides ease and convenience with small adjustments for quick attachment mounting.
- Heavy duty, pin style sway bars keep your attachment securely in place.



CONVENIENCE DESIGNED-IN

- Lower fuel tank positioning allows for quick and easy fueling.
- Larger fuel capacity increases productivity in the field.
- Keep you working longer between stops.

YANMAR YM342 Tractor Specifications

ENGINE	
Manufacturer	YANMAR
Model	4TNV88C-XKITL
Engine (hp)	41.4
PTO (hp)	31.0
Fuel Tank Capacity (gal)	13.2
Engine Displacement (ci)	133.6
Fuel	Diesel
Dual Air Cleaner Element	•
Large Volume Water Separator	•
One-Piece Full Open Hood	•

DIMENSIONS

Dimensiona	
Minimum Ground Clearance (in)	15.5
Wheelbase (in)	74.8
Front Tread (in) (R1 Tires)	50
Minimum Rear Tread (in) (R1 Tires)	52
Maximum Rear Tread (in) (R1 Tires)	64
Rear Adjustment Width (in) (R1 Tires)	12
Turning Radius (Without Brakes) (in) (R1 Tires)	138

WEIGHT ROPS (

OPS (lbs)	3,916

TRANSMISSION

Main Clutch	Dry Single
Main Shift	Synchronized
Reverser	Synchronized
Number of Gears (F-R)	F8 - R8
Maximum Traveling Speed (mph) (R1 Tires)	17.7

HYDRAULICS

Hitch Category (SAE Designation)	Category 1 & 2
Lower Link Ends	Telescopic
Remote Control Valves Available	1 Standard (2 Opt)

HYDRAULIC PUMP CAPACITY

Power Steering (gpm)	5.3
Implement (gpm)	9.3
Total (gpm)	14.6

POWER TAKE OFF

Speeds (rpm)	
Independent PTO	

3 POINT LIFT CAPACITY

Lower-Link Standard (lbs)	3,190
24" Behind (lbs)	2,750

TIRE SIZE

AG Front	8.0 - 16.0
AG Rear	14.9 - 24.0
Industrial Front	10.0 - 16.5
Industrial Rear	17.5L - 24.0
Turf Front	27.0 - 10.5
Turf Rear	44 x 18 - 20.0

EXTERIOR

©2022 Yanmar America Corporation. YT22-342

Full Flat Floor	•
Deluxe Seat	•
Cup Holder	•

To learn more or to find the dealer nearest you, please visit **YanmarTractor.com**.





Yanmar has a corporate policy of continuous product improvement and development; therefore data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating a machine, read, understand, and follow all instructions of the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.

540/540E

YANMAR YL605 LOADER SPECIFICATIONS

Maximum Lift Height (in)	113.0
Loader Weight (lb)	1,212.5
Dump Clearance (in)	87.6
Maximum Height @ Reach (in)	16.0
Reach with Bucket on Ground (in)	74.0
Digging Depth (in)	7.5
Maximum Dump Angle (Degree)	45°
Maximum Rollback Angle (Degree)	40°

PERFORMANCE

Lift Capacity (Pivot Pin) (lbs)	2,500
Lift Capacity (500 mm Foward) (lbs)	1,795
Breakout Force (500 mm Foward) (lbs)	3,047
Bucket Capacity (cu. ft.)	10.9

STANDARD

Skid Steer Quick Attach	•
Bucket Level Indicator	•
72" Bucket	•
Grille Guard	•

OPTIONAL

3rd Function Valve

YANMAR B85 BACKHOE SPECIFICATIONS

Backhoe Weight (lb)	1,818.8
Maximum Digging Depth (in)	103.0
Reach from Swing Pivot (in)	141.0
Transportation Height (in)	94.0
Transportation Length (in)	55.0
Bucket Digging Force (lbs)	4,600
Dipperstick Digging Force (lbs)	2,940
Digging Depth 2' Flat Bottom (in)	102.0
Loading Height (in)	83.0
Loading Reach (in)	61.0

Note: Buckets available in the following sizes, 12", 18" and 24".

AVAILABLE ATTACHMENTS FOR THE YANMAR YM342

Front End Loader	Grading Scraper	Rotary Cutter
Backhoe	Disc Harrow	3 Pt Attachments
Box Scraper	Pallet Forks	

Note: Attachments sold separately. Please see your dealer for details.

DEALERS WHO SHARE OUR COMMITMENT

Yanmar tractors are sold and serviced by a network of dealers who are committed to serving the communities in which they live and work. They share our passion for the land as well as a passion for unsurpassed service. To find the dealer nearest you, please visit YanmarTractor.com.