



CS-500P Chain Saw

User-Friendly Features and a Performance Cutting System



- Lightest 50 cc Gas Powered Engine Chain Saw in North America
- Spring-Assist Starter System
- Heavy-duty, Easy-Access Air Filter
- Dual Post Chain Brake System
- G-Force Engine Air Pre-Cleaner™
- Automatic Clutch-Driven Oiler
- Anti-Vibration System
- Aluminum Handle with Rubber Overmold
- Performance Cutting System™ Bar and Chain

All ECHO Chain Saws feature a 5 year* consumer, 1 year commercial and 90 day rental warranty as well as a lifetime warranty on the ignition module.

*Visit www.echo-usa.com/5year to learn more.

WWW.ECHO-USA.COM



Model CS-500P

The CS-500P Chain Saw is the lightest 50 cc gas powered engine in North America that, when coupled with the Performance Cutting System™ bar and chain, delivers outstanding cutting ability. It also features a spring-assist starter system that provides quick and effortless starts, a heavy-duty, easy-access air filter that provides superior filtration for long engine life, a dual post chain brake system for increased durability, the G-Force Engine Air Pre-Cleaner™ that pulls dust and chips from the air box providing a clean air supply to the engine, an automatic clutch-driven oiler that reduces oil consumption, an aluminum handle with rubber overmold and an anti-vibration system for reduced operator fatigue.



ECHO Quality Backed by an Extensive Warranty

All ECHO Chain Saws feature a 5 year* consumer, 1 year commercial and 90 day rental warranty as well as a lifetime warranty on the ignition module.

*Visit www.echo-usa.com/5year to learn more.



| Model | Engine Displacement (cc) | Engine Displacement (cu in) | Starting System | Ignition System | Purge Bulb | Oiling System | Vibration Reduction System | Available Bar Lengths (in) | Fuel Capacity (fl oz) | Oil Capacity (fl oz) | Dry Weight* (lb) |
|-------------|--------------------------|-----------------------------|-----------------|-----------------|------------|-------------------------|----------------------------|----------------------------|-----------------------|----------------------|------------------|
| CS-271 | 26.9 | 1.64 | i-30™ | Digital | Yes | Automatic/Adjustable | Standard | 12 | 8.1 | 5.4 | 6.6 |
| CS-310 | 30.5 | 1.86 | i-30™ | Digital | Yes | Automatic ** | Standard | 14 | 8.5 | 8.8 | 8.8 |
| CS-330T | 32.6 | 1.99 | Standard | Digital | No | Automatic/Adjustable | Standard | 12, 14, 16 | 10.5 | 9.8 | 8.1 |
| CS-341 | 33.4 | 2.04 | Standard | SAIS | Yes | Automatic/Adjustable | Standard | 12, 14, 16 | 8.5 | 5.0 | 7.6 |
| CS-352 | 34.0 | 2.08 | i-30™ | Digital | Yes | Automatic ** | Standard | 14, 16 | 8.5 | 8.8 | 8.8 |
| CS-360T | 36.3 | 2.21 | Standard | Digital | No | Automatic/Adjustable | Standard | 12, 14, 16 | 10.5 | 9.8 | 8.1 |
| CS-370 | 36.3 | 2.21 | i-30™ | Digital | Yes | Automatic/Adjustable | Standard | 14, 16, 18 | 13.9 | 9.5 | 10.0 |
| CS-400 | 40.2 | 2.45 | i-30™ | Digital | Yes | Automatic/Adjustable | Standard | 16, 18 | 13.9 | 9.5 | 10.1 |
| CS-450/450P | 45.0 | 2.75 | Standard | Digital | No | Automatic/Adjustable** | Standard | 16, 18, 20 | 15.2 | 9.5 | 11.2 |
| CS-500P | 50.2 | 3.06 | Spring-assist | CDI | No | Automatic/Adjustable** | Standard | 16, 18, 20 | 16.9 | 9.5 | 10.6 |
| CS-550P | 54.1 | 3.30 | Standard | Digital | No | Automatic/Adjustable** | Standard | 16, 18, 20 | 17.9 | 10.1 | 13.3 |
| CS-600P | 59.8 | 3.65 | Standard | Digital | No | Automatic/Adjustable** | Standard | 20, 24, 27 | 19.1 | 10.1 | 13 |
| CS-680 | 66.8 | 4.07 | Standard | SAIS | No | Automatic/Adjustable*** | Standard | 20, 24, 27 | 22.5 | 13.0 | 14.5 |

*without bar and chain

** clutch-driven

*** with manual override