



## SRM-280 SERIES TRIMMERS

### A New Class of Performance



5 year consumer, 1 year commercial  
and 90 day rental warranty.

TRIMMERS



- 28.1cc Power Boost Vortex™ Engine Combines Power with Light Weight
- Ergonomically Comfortable for Extended Use
- Rubber Handles for a Comfortable Grip
- Commercial-grade Felt Air Filtration for Improved Air Quality and Increased Engine Performance
- Blade-Use Convertible with Optional Kit
- Available in a Variety of Configurations

SRM-280 Model Shown

# SRM-280 SERIES TRIMMERS

The SRM-280 Series of Trimmers, all in a bold new color, represents an entire new class of performance for ECHO Trimmers. ECHO's new 28.1cc engine class delivers increased power combined with light weight. And that means better performance. The units are available in standard (SRM-280), steel shaft (SRM-280S), high torque (SRM-280T), or "U"-handle (SRM-280U) configurations. Common features to all include: a powerful 28.1cc Power Boost Vortex™ engine for plenty of performance, rubber left and right handle grips for comfortable all day operation, and commercial-grade felt air filtration for improved air quality and increased engine durability.



5 year consumer,  
1 year commercial, and  
90 day rental warranty



A powerful, smooth-running 28.1cc Power Boost Vortex™ engine delivers performance.

A rubber throttle handle provides comfortable all day operation. The left hand grip is also rubber-coated.

An ECHOmatic Pro™ trimmer head equipped with .095" diameter Cross-Fire® line makes quick work of any trimming job.

Model	Engine Displacement (cc)	Carburetor (w/Purge Pump)	Fuel Capacity (fl oz)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Cutting Swath (in)	Shield	Drive Shaft	Nylon Line (in dia)	Dry Weight (lb)*	Dry Weight (lb)**
GT-200R/201R	21.2	Rotary	15.2	48	Curved	i-30™	Rapid-Loader™	16	Std. GT	4Layer Cable	.080 CrossFire®	9.3/9.6	8.8/9.1
GT-200i/201i	21.2	Rotary	15.2	48	Curved	i-75™	Rapid-Loader™	16	Std. GT	4Layer Cable	.080 CrossFire®	9.6/9.9	8.8/9.1
GT-251E/251	25.4	Diaphragm	14.2	52	Curved	i-30™	Rapid-Loader™	16	Std. GT	Flexible	.080 CrossFire®	10.4/10.6	9.9/10.1
SRM-210/211	21.2	Rotary	15.2	59	Straight	i-30™	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	11.4/11.6	10.6/10.8
SRM-210i/211i	21.2	Rotary	15.2	59	Straight	i-75™	Rapid-Loader™	17	Std. SRM	4Layer Cable	.095 CrossFire®	11.6/11.8	10.9/11.1
SRM-210SB	21.2	Rotary	15.2	59	Split Shaft	i-30™	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	11.9	11.1
SRM-230/231	22.8	Rotary	19.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	12.2/12.4	11.4/11.6
SRM-230S/231S	22.8	Rotary	19.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	Steel	.095 CrossFire®	12/12.2	11.2/11.4
SRM-251E/251	25.4	Diaphragm	14.2	59	Straight	i-30™	ECHOmatic Pro™	17	Std. SRM	Flexible	.095 CrossFire®	11.3/11.5	10.5/10.7
SRM-260/261	25.4	Rotary	19.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	12.5/12.7	11.1/11.3
SRM-260S	25.4	Rotary	19.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	Steel	.095 CrossFire®	12.0/12.2	10.7/10.9
SRM-261T	25.4	Rotary	19.6	59	Straight	Standard	ECHOmatic™	17	Std. SRM	4Layer Cable	.095 CrossFire®	12.8	10.9
SRM-265	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	13.4	12.3
SRM-265S	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOmatic Pro™	17	Std. SRM	Steel	.095 CrossFire®	12.9	12.1
SRM-265T	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOmatic™	17	Std. SRM	4Layer Cable	.095 CrossFire®	13.7	12.7
SRM-265U	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	14.4	13.5
SRM-280	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	13.5	12.6
SRM-280S	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	Steel	.095 CrossFire®	13.4	12.5
SRM-280T	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOmatic™	17	Std. SRM	4Layer Cable	.095 CrossFire®	13.6	12.7
SRM-280U	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOmatic Pro™	17	Std. SRM	4Layer Cable	.095 CrossFire®	14.5	13.6
SRM-311	30.5	Diaphragm	30.4	59	Straight	Standard	ECHOmatic™	17	Std. SRM	4Layer Cable	.095 CrossFire®	14.5	13.7
SRM-311S	30.5	Diaphragm	30.4	59	Straight	Standard	ECHOmatic II™	17	Std. SRM	Steel	.105 CrossFire®	15.5	14.4
SRM-340	34	Diaphragm	27.1	60.2	Straight	Standard	ECHOmatic II™	17	Std. SRM	Steel	.105 CrossFire®	16	14.9

\* Includes cutting head, excludes harness

\*\* Without cutting head, includes shield