

H&S

FLEX-FRAME RAKES

**Flex-Frame Rakes
are available in 16, 18, 20, &
22 Wheel Models!**



Model 6122

6116 FLEX-FRAME Rake Specifications

Number of Wheels	16
Wheel Diameter	60"
Teeth per Wheel	40
Tooth Diameter	7.5mm
Rake Wheel Hubs	Ball Bearings
Rake Wheel Anti-wrap Shields	Standard
Rake Wheel Suspension	Independent "Bee Hive" Spring
Transport Width	10'6"
Transport Length	Approx. 32'7"
Transport Height in Transport Position	80" w/SMV Sign
Maximum Raking Width	Approx. 32'
Windrow Width Adjustment	3' – 5'
Number of Raking Positions	6
Ground Pressure Rake Wheel Adjustment	Nut/Threaded Rod for fine tuning
Rake Wheel Wind Panels	Standard
Hydraulic Rear Windrow Adjustment	Optional - Additional Remote Needed
Hitch Jack	Standard
Weight	5,750#
Center Kicker Wheel	Optional
Hydraulic Requirements	1 Double Acting Cylinder for Folding
Front Gauge Wheels	4 - 9.5L x 15
Standard Single Rear Transport Wheels	2 - 9.5L x 15
Optional Tandem Rear Transport Wheels	4 - 9.5L x 15
Transport Lighting	Optional



Model 6116

FLEX-FRAME RAKE FEATURES



Rake Arm Flex-Joint



Rake Beam Flex-Joint



**Optional Hydraulic Rear
Windrow Adjustment**

6118/6120/6122 FLEX-FRAME Rake Specifications

Model	6118	6120	6122
Number of Wheels	18	20	22
Wheel Diameter	-----60"-----		
Teeth per Wheel	-----40-----		
Tooth Diameter	-----7.5mm-----		
Rake Wheel Hubs	-----Ball Bearings-----		
Rake Wheel Anti-wrap Shields	-----Standard-----		
Rake Wheel Suspension	-----Independent "Bee Hive" Spring-----		
Transport Width	-----11'6"-----		
Transport Length	Appox. 34'8"	Appox. 37'6"	Appox. 40'6"
Transport Height in Transport Position	-----N/A-----		
Maximum Raking Width	Appox. 35'6"	Appox. 38'6"	Appox. 41'6"
Windrow Width Adjustment	-----3' - 5'-----		
Number of Raking Positions	-----6-----		
Ground Pressure Rake Wheel Adjustment	-----Nut/Threaded Rod for fine tuning-----		
Rake Wheel Wind Panels	-----Standard-----		
Hydraulic Rear Windrow Adjustment	-----Optional - Additional Remote Needed-----		
Hitch Jack	-----Standard-----		
Weight	7,894#	8,224#	8,521#
Center Kicker Wheel	-----Optional-----		
Hydraulic Requirements	-----1 Double Acting Cylinder for Folding-----		
	-----1 Double Acting Cylinder for Rake Wheel Lift-----		
Front Gauge Wheels	-----4 - 11L x 15-----		
Standard Single Rear Transport Wheels	-----2 - 11L x 15-----		
Optional Tandem Rear Transport Wheels	-----4 - 11L x 15-----		
Transport Lighting	-----Optional-----		

H&S Manufacturing

Ph. #715.387.3414

Web: www.hsmfgco.com

Models & Specifications are subject to change without prior notice.

HSMFG62216